



Item # _____

Job _____



Casters — Stem Type

METRO® STEM CASTERS

- **Metro Stem-Type Casters** are designed to fit Super Erecta Shelf® posts to form shelf carts and other mobile units.
- **Stainless Steel, Cart-Washable Casters** offer grease seals and zerk fittings. Can withstand high-pressure washings.
- **Polymer Horn Casters:** Innovative polymer stem casters offer corrosion resistance and enhanced durability. For all medium-duty applications.
- **Resilient Rubber Tread:** A molded, soft tread that provides good floor protection along with quiet operation. Non-marking.
- **Polyurethane Tread:** Long-wearing; resists abrasion. Non-marking, shock absorbing.
- **Wheel Brakes:** Foot-operated. Available on all caster models.
- **Caster Load Ratings:** From 125 lbs. to 300 lbs. (57 to 136kg) See chart.
- **Donut Bumpers:** Furnished standard on all Metro stem casters.
- **Additional Caster Types Available.**

Note: SPECIAL WHEELS — V-groove, Conductive, Steel and Phenolic — are available on request. For additional information, contact InterMetro Industries Corporation or your InterMetro representative.

Resilient Rubber




5MB Wheel Brake



5M Resilient

Stainless Steel, Cart Washable



5MDGSA

Polymer Horn Casters



5PC



InterMetro Industries Corporation
North Washington Street
Wilkes-Barre, PA 18705
www.metro.com



11.20



METRO® STEM CASTERS

Standard Casters — Stem Type

| Model No. | Wheel Diameter (in.) (mm) | Face (in.) (mm) | Load Rating (lbs.) (kg) | Type | Wheel Tread | Approx. Pkd. Wt. (lbs.) (kg) |
|-----------|------------------------------|--------------------|----------------------------|-------------|--------------------|------------------------------------|
| 4LD | 4 102 | 1/2 12 | 125 56 | Stem/Swivel | Resilient | 1 1/2 .6 |
| 5LD | 5 127 | 1/2 12 | 125 56 | Stem/Swivel | Resilient | 2 .9 |
| 5M | 5 127 | 1 1/4 32 | 200 90 | Stem/Swivel | Resilient | 2 1/2 1.1 |
| 5MB | 5 127 | 1 1/4 32 | 200 90 | Stem/Brake | Resilient | 2 5/8 1.2 |
| 5MR | 5 127 | 1 1/4 32 | 200 90 | Stem/Rigid | Resilient | 3 1/2 1.5 |
| 5MDA | 5 127 | 1 1/4 32 | 250 111 | Stem/Swivel | High Modulus Donut | 2 1/2 1.1 |
| 5MDBA | 5 127 | 1 1/4 32 | 250 111 | Stem/Brake | High Modulus Donut | 2 5/8 1.17 |
| 5MDRA | 5 127 | 1 1/4 32 | 250 111 | Stem/Rigid | High Modulus Donut | 2 3/8 1.08 |
| 5MP | 5 127 | 1 1/4 32 | 300 135 | Stem/Swivel | Polyurethane | 2 1/8 .94 |
| 5MPB | 5 127 | 1 1/4 32 | 300 135 | Stem/Brake | Polyurethane | 2 1/4 1 |
| 5MPR | 5 127 | 1 1/4 32 | 300 135 | Stem/Rigid | Polyurethane | 2 .9 |
| 6MP | 6 152 | 1 1/2 38 | 400 182 | Stem/Swivel | Polyurethane | 2 1/4 1.08 |
| 6MPB | 6 152 | 1 1/2 38 | 400 182 | Stem/Brake | Polyurethane | 2 1/2 .94 |
| 6MPR | 6 152 | 1 1/2 38 | 400 182 | Stem/Rigid | Polyurethane | 2 1/4 1 |

Note 1: Rigid casters are held in position by a connecting channel. When ordering rigid casters, shelf width must be known.

Note 2: Load Height for all 5M and 5MP casters — $6\frac{7}{32}'' \pm \frac{1}{16}''$ (155 ± 1.5mm).

Note 3: Load Height for 4LD caster — $4\frac{5}{8}'' \pm \frac{1}{16}''$ (118 ± 1.5mm).

Note 4: Load Height for 5LD caster — $5\frac{5}{8}'' \pm \frac{1}{16}''$ (143 ± 1.5mm).

Note 5: Brakes are foot-operated.

Polymer Casters — Stem Type

| Model No. | Model No. Antimicrobial | Wheel Tread | Face Type | Load Rating (in.) (mm) | Approx. Pkd. Wt. (lbs.) (kg) | Temp Range (lbs.) (kg) | (continuous) |
|-----------|----------------------------|--------------|--------------|---------------------------|------------------------------------|---------------------------|----------------|
| 5PC | 5PCM | Polyurethane | Swivel | 1 1/4 32 | 300 135 | 2 .9 | -20°F to 120°F |
| 5PCB | 5PCBM | Polyurethane | Brake | 1 1/4 32 | 300 135 | 2 .9 | -20°F to 120°F |
| 5PCR | | Polyurethane | Rigid | 1 1/4 32 | 300 135 | 2 .9 | -20°F to 120°F |

Note 1: Rigid casters are held in place by a connecting channel. When ordering, shelf depth must be provided.

Stainless Steel Cart-Washable Casters — Stem Type

| Model No. | Wheel Diameter (in.) (mm) | Face (in.) (mm) | Load Rating (lbs.) (kg) | Type | Wheel Tread | Approx. Pkd. Wt. (lbs.) (kg) |
|-----------|------------------------------|--------------------|----------------------------|--------|--------------------|------------------------------------|
| 5MDGSA | 5 127 | 1 1/4 32 | 250 111 | Swivel | High Modulus Donut | 2 1/2 1.1 |
| 5MDBGSA | 5 127 | 1 1/4 32 | 250 111 | Brake | High Modulus Donut | 2 5/8 1.17 |
| 5MDRGSA | 5 127 | 1 1/4 32 | 250 111 | Rigid | High Modulus Donut | 2 3/8 1.08 |
| 5MPGSA | 5 127 | 1 1/4 32 | 300 135 | Swivel | Polyurethane | 2 1/8 .94 |
| 5MPBGSA | 5 127 | 1 1/4 32 | 300 135 | Brake | Polyurethane | 2 1/4 1 |
| 5MPRGSA | 5 127 | 1 1/4 32 | 300 135 | Rigid | Polyurethane | 2 .9 |

Note 1: Rigid casters are held in position by a connecting channel. When ordering rigid casters, shelf width must be known.

Note 2: Load Height for all 5MD and 5MP casters — $6\frac{7}{32}'' \pm \frac{1}{16}''$ (155 ± 1.5mm).

Note 3: All casters are grease sealed with zerk fittings in swivel and axle.

Note 4: Brakes are foot-operated.

All Metro Catalog Sheets are available on our website: www.metro.com



InterMetro Industries Corporation

North Washington Street, Wilkes-Barre, PA 18705

Phone: 570-825-2741

Product Information. U.S. and Canada: 1.800.992.1776

Outside U.S. and Canada: www.metro.com/contactus

L02-041

Printed in U.S.A. Rev. 1/15

Information and specifications are subject to change without notice. Please confirm at time of order

Copyright © 2015 InterMetro Industries Corp.