



Item # \_\_\_\_\_

We put space to work.

Job \_\_\_\_\_

The MetroMax i<sup>®</sup> Drying Rack combines the corrosion resistance and strength of MetroMax i with the convenience of a drying rack unit that efficiently holds pots, pans and trays while they dry.

- All polymer construction with Type 304 Stainless Steel wire drop-in shelves. Posts and shelves offer a lifetime warranty against rust and corrosion. Corrosion-resistant, epoxy-coated tray drying racks.
- PR48VX3 and PR48X3 models come with two intermediate stainless steel shelves that provide maximum space utilization for pots, pans, and lids. Top shelf features an epoxy coated tray drying rack with 34 slot capacity. The open grid bottom shelf is great for drying large stock and lobster pans.
- PR48VX4 and PR48X4 models come with four epoxy coated tray drying racks: Two with 34 slots each at 1-1/8" (29mm) spacing for trays, cutting boards and lids. Two with 14 slots each at 3" (76mm) spacing for steam and bun pans.
- Easy to clean: MetroMax i<sup>®</sup> open-grid shelf mats lift off easily and fit in the dish machine. Stainless Steel wire drop-ins and tray drying racks clean easily by hand with mild detergents.
- Shelves are adjustable at 1" (25mm) increments along the height of the numbered posts.
- Shelf mats, posts and epoxy coated tray drying racks have built-in Microban antimicrobial product protection. It keeps the product "cleaner between cleanings".
- Corrosion-resistant polymer casters option allows for easy cleaning and mobility.

**Key Benefits**

- Fast drying of trays, cutting boards, pans, lids, pots and all sink items.
- Promotes food safety by preventing wet nesting, where two wet/damp items are nested together preventing proper airflow.
- Superior air circulation.
- Interchangeable shelves adapt to all environments.
- Efficient organized drying area.
- Mobile units allows for easy floor clean-up and transportability.



Mobile



Mobile



Inhibits the growth of stain and odor causing bacteria. Microban<sup>®</sup> does not protect users from food borne illness. Normal cleaning practices should be maintained. Microban is a registered trademark of Microban Products Company.

All Metro Catalog Sheets are available on our website: [www.metro.com](http://www.metro.com)



**InterMetro Industries Corporation**  
North Washington Street, Wilkes-Barre, PA 18705  
Product Information. U.S. and Canada: 1.800.992.1776  
Outside U.S. and Canada: [www.metro.com/contactus](http://www.metro.com/contactus)

L02-185  
Printed in U.S.A. 10/17

Information and specifications are subject to change without notice. Please confirm at time of order.

Copyright © 2017 InterMetro Industries Corp.



**MetroMax i<sup>®</sup> Drying Rack Units**

**9.31**



# MetroMax i<sup>®</sup> DRYING RACK UNITS

We put space to work.<sup>®</sup>

## Specifications

- **Longitudinal Beams & Posts:** Pultrusions — continuous glass fibers and thermo set resin composite with built-in Microban antimicrobial product protection. Exterior surfaces are high-impact thermoplastic resin.
- **End Beams, Adjustable Foot & Socket:** Injection molded polyester thermoplastic resin with glass reinforcement.
- **Drop In — Electro-Polished Type 304 Stainless Steel**
- **Cutting Board/Tray Drying Rack:** Corrosion resistant taupe epoxy coated steel with built-in Microban product protection.
- **Shelf Mats:** Polypropylene. Mats contain Microban antimicrobial product protection.
- **Stationary Load Capacity:**  
300 lbs. (136kg) per wire grid  
800 lbs. (363kg) per shelf
- **Mobile Load Capacity:**  
800 lbs. (363kg) per shelf  
300 lbs. (136kg) per wire grid  
900 lbs. (408kg) per unit
- **Polymer Casters:** 2 swivel, 2 brake. Corrosion-resistant, polymer horn, stainless steel axle and hardware. 5" (127mm) diameter.

## Dimensions

### MetroMax i<sup>®</sup> Stationary Drying Rack Unit

Model No.	Width		Length		Height		Approx. Pkd. Wt.	
	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)
PR48X3	24	610	48	1219	75 <sup>1</sup> / <sub>2</sub>	1917.5	130	59
PR48X4	24	610	48	1219	75 <sup>1</sup> / <sub>2</sub>	1917.5	142	64

PR48X3 includes two drop-ins and one cutting board/tray drying rack

PR48X4 includes two cutting board/tray drying racks and two drying racks for 2<sup>1</sup>/<sub>2</sub>" (64mm) deep steam table pans.

### MetroMax i<sup>®</sup> Mobile Drying Rack Unit

Model No.	Width		Length		Height		Approx. Pkd. Wt.	
	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)	(lbs.)	(kg)
PR48VX3	26	660	50	1270	68	1702	124	56
PR48VX4	26	660	50	1270	68	1702	148	67

PR48VX3 includes two drop-ins and one cutting board/tray drying rack

PR48VX4 includes two cutting board/tray drying racks and two drying racks for 2<sup>1</sup>/<sub>2</sub>" (64mm) deep steam table pans.

Dimensions include caster bumpers

### Cutting Board/Tray Drying Rack and Stainless Drop-In Components

- Use to create a unique configuration to fit the application.

### Cutting Board & Tray Drying Rack System

- Mount to open grid and solid MetroMax i<sup>®</sup> shelves or open grid MetroMax Q<sup>®</sup> shelves
- 1<sup>1</sup>/<sub>8</sub>" (28mm) or 3" (76mm) slot spacing available.

i and Q Model No.	Fits Shelf		Upright Spacing (in.)	Upright Spacing (mm)	Upright Height		Tray Capacity	Approx. Pkd. Wt.	
	(in.)	(mm)			(in.)	(mm)		(lbs.)	(kg)
MTR2436XE	24x36	610x914	1 <sup>1</sup> / <sub>8</sub>	28	6	150	24	13.5	6.1
MTR2448XE	24x48	610x1219	1 <sup>1</sup> / <sub>8</sub>	28	6	150	34	18.0	8.2
MTR2460XE	24x60	610x1524	1 <sup>1</sup> / <sub>8</sub>	28	6	150	42	22.5	10.2
MTR2436XEA	24x36	610x914	3	76	6	150	10	9.8	4.4
MTR2448XEA	24x48	610x1219	3	76	6	150	14	13	5.9
MTR2460XEA	24x60	610x1524	3	76	6	150	17	16.3	7.4

**Note:** Can be retrofitted to original MetroMax<sup>®</sup> and MetroMax Q<sup>®</sup>.

### Type 304 Stainless Drop-In Racks

- Drop-ins require a four-sided MetroMax i<sup>®</sup> frame and center beam. See spec sheet 9.25 for open frame and center beam part numbers
- A drop-in rack can be added to a standard MetroMax i<sup>®</sup> shelf by removing the shelf mats and using the shelf frame and center beam.

i and Q Model No.	Width		Length		Height		Wire Spacing (in.)	Wire Spacing (mm)	Approx. Pkd. Wt.	
	(in.)	(mm)	(in.)	(mm)	(in.)	(mm)			(lbs.)	(kg)
DR36S	24	610	33 <sup>7</sup> / <sub>8</sub>	860	5 <sup>1</sup> / <sub>4</sub>	133	<sup>3</sup> / <sub>4</sub>	19	9	4.1
DR48S	24	610	45 <sup>7</sup> / <sub>8</sub>	1165	5 <sup>1</sup> / <sub>4</sub>	133	<sup>3</sup> / <sub>4</sub>	19	12	5.4
DR60S	24	610	57 <sup>7</sup> / <sub>8</sub>	1470	5 <sup>1</sup> / <sub>4</sub>	133	<sup>3</sup> / <sub>4</sub>	19	15	6.8

