

TANKLESS ELECTRIC WATER HEATER FOR HAND SINKS 7-PS-92

FEATURES:

Unlimited supply of hot water (No water storage tank required) Only 1 single supply line of cold water is required to feed the unit. Single shut off valve for ease of service.

Scald Guard Technology keeps water temperature within safe limits at all times.

Includes Fittings and Supply Lines for Faucet

SPECIFICATIONS:

ETL listed (water heater only). 120 volts / single phase / Must Be Hard Wired. Wattage 3.0 kw.

Amps = 25 (Required circuit breaker size: 30 amps).

Electrical Connection to Circuit Breaker Panel Box By Others.

Max. water pressure = 150 psi.

Gallons per minute = 0.5

Temperature rise @ 0.5 gpm = 41 degrees.

IMPORTANT NOTES:

Must Specify Hand Sink Model When Ordering to ensure proper fittings and faucet supply lines.

Depending on incoming water pressure, it may be required to adjust the cold water Inlet Valve to achieve the temperature required.

ADDITIONAL NOTES FOR FOOT & KNEE VALVE HAND SINKS:

Factory Installed Only in Pedestal Base Units.

If desired temperature is not reached, adjust the hot water Mixing Valve that is on the Foot or Knee Pedal.



Heater Shown installed with a Hand Sink (Sink sold seperately)

Item #: _____ Qty #: _____

Model #:_____

Project #:_____



Heater Shown installed in a Pedestal Base Unit (Sink sold seperately. Must be Factory Installed)



Heater feeds hot and cold water supply to the Valve in Pedestal Base and Knee Valve Units (Pedal Valve Shown)



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T. Email Orders To: customer@advancetabco.com. For Smart Fabrication™ Quotes, Email To: smartfab@advancetabco.com or Fax To: 631-586-2933

 NEW YORK
 GEORGIA
 TEXAS
 NEVADA

 Fax: (631) 242-6900
 Fax: (770) 775-5625
 Fax: (972) 932-4795
 Fax: (775) 972-1578

ADVANCE TABCO is constantly engaged in a program of improving our products. Therefore, we reserve the right to change specifications without prior notice.