

PRODUCT:

QUANTITY:

Stationary Models  SST-2S  SST-3S  SST-4S  SST-5S  
 Portable Models  PSST-2S  PSST-3S  PSST-4S  PSST-5S  
 ITEM:

## Designed Smart

APW Wyott® Hot Well Sealed Element Steam Tables individual sealed wells are fully coved and constructed of type 304 stainless steel.

- Individual infinite switch heat controls; thermostatic also available
- Indicator light remains on while control is in ON position
- Standard with 750 watt elements; 1200 and 1600 watt elements are available
- Deep drawn type 304 stainless steel well
- Fully welded drain
- Copper manifold with gate valve is standard
- ½" thick poly cutting board mounted on stainless steel shelf supported by stainless steel brackets
- Available with stainless steel legs and under shelf
- Cord and plug included with standard units



Model: SST5

## APW Wyott Design Features

Heavy gauge stainless steel construction for the body. Individual controls allow for wet or dry application.

Features include:

- Poly cutting board
- Stainless steel undershelf with legs
- High-output tubular heating elements.
- Stationary and portable units available.
- UL and UL Sanitation approved
- Full range of options and accessories.
- All wells complete with drains running to a common all-copper manifold complete with ball valve

## Reliability Backed by APW Wyott's Warranty

All APW Wyott cooking equipment is backed by a 1-year limited warranty and a 1-year on-site labor warrant. \*

Certified by the following agencies:



## Options and Accessories

### Cutting Boards

- NSF approved Plastic Cutting Boards – 7 1/2" X 12"
- Hardwood – 8" X 1-1/4"
- Richlite Heat-Resistant – 8" X 12"
- Stainless Steel Dish Shelf
- Serving Shelves with Glass Protector
- Plate Shelves
- Tubular Tray Slide – 3-Bar
- Buffet Shelves
- Spillage Pans
- Adjustable Overall Shelf System
- Deluxe Serving Shelves
- Solid Tray Slide
- Roll-top Covers
- Adapter Bars for Food Pans – 10" X 12"
- Adapter Tops for Round Inserts – 4-, 7-, and 11-Quart

Stationary Models  SST-2  SST-2S  SST-3  SST-3S  SST-4  SST-4S  SST-5  SST-5S  
 Portable Models  PSST-2  PSST-2S  PSST-3  PSST-3S  PSST-4  PSST-4S  PSST-5  PSST-5S

## PRODUCT SPECIFICATIONS

### Construction:

Individual sealed wells are fully covered and constructed of type 304 stainless steel.

**Freight Class:** 100

**FOB:** Allen, TX 75013

### Stationary

Non-Marking feet adjust unit height from 34 ½" to 35 ½".

Dimensions						
Model	# of top openings	Length	Width	Height	Weight	Electrical Data
SST-120-2S	2	31 3/8"	22 ½"	34	140	1500W, 120V, 12.5A
SST-208-2S	2	31 3/8"	22 ½"	34	140	1500W, 208V, 7.21A
SST-240-2S	2	31 3/8"	22 ½"	34	140	1500W, 240V, 6.25A
SST-120-3S	3	45 ¾"	22 ½"	34	180	2250W, 120V, 18.8A
SST-208-3S	3	45 ¾"	22 ½"	34	180	2250W, 208V, 10.82A
SST-240-3S	3	45 ¾"	22 ½"	34	180	2250W, 240V, 11.9A
SST-120-4S	4	60 1/8"	22 ½"	34	225	3000W, 120V, 25A
SST-208-4S	4	60 1/8"	22 ½"	34	225	3000W, 208V, 14.42A
SST-240-4S	4	60 1/8"	22 ½"	34	225	3000W, 240V, 15.8A
SST-120-5S	5	74 ½"	22 ½"	34	260	3750W, 120V, 31.3A
SST-208-5S	5	74 ½"	22 ½"	34	260	3750W, 208V, 18.3A
SST-240-5S	5	74 ½"	22 ½"	34	260	3750W, 240V, 19.8A

### Portable

Push handle and 4" – diameter casters, two with brake included

Dimensions						
Model	# of top openings	Length	Width	Height	Weight	Electrical Data
PSST-120-2S	2	31 3/8"	22 ½"	34	140	1500W, 120V, 12.5A
PSST-208-2S	2	31 3/8"	22 ½"	34	140	1500W, 208V, 7.21A
PSST-240-2S	2	31 3/8"	22 ½"	34	140	1500W, 240V, 6.25A
PSST-120-3S	3	45 ¾"	22 ½"	34	180	2250W, 120V, 18.8A
PSST-208-3S	3	45 ¾"	22 ½"	34	180	2250W, 208V, 10.82A
PSST-240-3S	3	45 ¾"	22 ½"	34	180	2250W, 240V, 11.9A
PSST-120-4S	4	60 1/8"	22 ½"	34	225	3000W, 120V, 25A
PSST-208-4S	4	60 1/8"	22 ½"	34	225	3000W, 208V, 14.42A
PSST-240-4S	4	60 1/8"	22 ½"	34	225	3000W, 240V, 15.8A
PSST-120-5S	5	74 ½"	22 ½"	34	260	3750W, 120V, 31.3A
PSST-208-5S	5	74 ½"	22 ½"	34	260	3750W, 208V, 18.3A
PSST-240-5S	5	74 ½"	22 ½"	34	260	3750W, 240V, 19.8A

### Receptacle configurations required for Sealed Well Food Tables.

15 AMP 125V model #	15 AMP 250V model #	20 AMP 250V model #	30 AMP 125V model #	30 AMP 250V model #	50 AMP 125V model #

NEMA 5-15 plug	NEMA 6-15 plug	NEMA 6-20 plug	NEMA 5-30 plug	NEMA 6-30 plug	NEMA 5-50 plug
----------------	----------------	----------------	----------------	----------------	----------------

\*APW Wyott reserves the right to modify specifications or discontinue models without incurring obligation.