

Stationary Models SST-2 SST-2S SST-3 SST-3S SST-4 SST-4S SST-5 SST-5S
 Portable Models PSST-2 PSST-2S PSST-3 PSST-3S PSST-4 PSST-4S PSST-5 PSST-5S
 PRODUCT: QUANTITY: ITEM:

Designed Smart

APW Wyott® Hot Well Sealed Element Steam Tables individual sealed wells are fully coved and constructed of type 304 stainless steel.

- Individual infinite switch heat controls; thermostatic also available
- Indicator light remains on while control is in ON position
- Standard with 750 watt elements; 1200 and 1600 watt elements are available
- Deep drawn type 304 stainless steel well
- Fully welded drain
- Copper manifold with gate valve is standard
- ½" thick poly cutting board mounted on stainless steel shelf supported by stainless steel brackets
- Available with either, stainless steel legs and under shelf or coated steel legs and under shelf
- Cord and plug included with standard units



Model: SST5

APW Wyott Design Features

Heavy gauge stainless steel construction for the body. Individual controls allow for wet or dry application.

Features include:

- Poly cutting board
- Stainless steel undershelf with legs
- High-output tubular heating elements.
- Stationary and portable units available.
- UL and UL Sanitation approved
- Full range of options and accessories.
- All wells complete with drains running to a common all-copper manifold complete with ball valve

Reliability Backed by APW Wyott's Warranty

All APW Wyott cooking equipment is backed by a 1-year limited warranty and a 1-year on-site labor warrant. *

Certified by the following agencies:



Options and Accessories

Cutting Boards

- NSF approved Plastic Cutting Boards – 7 1/2" X 12"
- Hardwood – 8" X 1-1/4"
- Richlite Heat-Resistant – 8" X 12"

- Stainless Steel Dish Shelf
- Serving Shelves with Glass Protector
- Plate Shelves
- Tubular Tray Slide – 3-Bar
- Buffet Shelves
- Spillage Pans
- Adjustable Overall Shelf System
- Deluxe Serving Shelves
- Solid Tray Slide
- Roll-top Covers
- Adapter Bars for Food Pans – 10" X 12"
- Adapter Tops for Round Inserts – 4-, 7-, and 11-Quart
- Auto Fill

Stationary Models SST-2 SST-2S SST-3 SST-3S SST-4 SST-4S SST-5 SST-5S
 Portable Models PSST-2 PSST-2S PSST-3 PSST-3S PSST-4 PSST-4S PSST-5 PSST-5S

PRODUCT SPECIFICATIONS

Construction:

Individual sealed wells are fully covered and constructed of type 304 stainless steel.

Freight Class: 100

FOB: Allen, TX 75013

Stationary

Non-Marking feet adjust unit height from 34 1/2" to 35 1/2".

Dimensions						
Model	# of top openings	Length	Width	Height	Weight	Electrical Data
SST-120-2 or 2S	2	31 3/8"	22 1/2"	34	140	1500W, 120V, 12.5A
SST-208-2 or 2S	2	31 3/8"	22 1/2"	34	140	1500W, 208V, 7.21A
SST-240-2 or 2S	2	31 3/8"	22 1/2"	34	140	1500W, 240V, 6.25A
SST-120-3 or 3S	3	45 3/4"	22 1/2"	34	180	2250W, 120V, 18.8A
SST-208-3 or 3S	3	45 3/4"	22 1/2"	34	180	2250W, 208V, 10.82A
SST-240-3 or 3S	3	45 3/4"	22 1/2"	34	180	2250W, 240V, 11.9A
SST-120-4 or 4S	4	60 1/8"	22 1/2"	34	225	3000W, 120V, 25A
SST-208-4 or 4S	4	60 1/8"	22 1/2"	34	225	3000W, 208V, 14.42A
SST-240-4 or 4S	4	60 1/8"	22 1/2"	34	225	3000W, 240V, 15.8A
SST-120-5 or 5S	5	74 1/2"	22 1/2"	34	260	3750W, 120V, 31.3A
SST-208-5 or 5S	5	74 1/2"	22 1/2"	34	260	3750W, 208V, 18.3A
SST-240-5 or 5S	5	74 1/2"	22 1/2"	34	260	3750W, 240V, 19.8A

Portable

Push handle and 4" – diameter casters, two with brake included

AutoFill® Automatic Water System

For AutoFill add "A" to the front of the Model number. Example: ASST-120-2

Dimensions						
Model	# of top openings	Length	Width	Height	Weight	Electrical Data
PSST-120-2 or 2S	2	31 3/8"	22 1/2"	34	140	1500W, 120V, 12.5A
PSST-208-2 or 2S	2	31 3/8"	22 1/2"	34	140	1500W, 208V, 7.21A
PSST-240-2 or 2S	2	31 3/8"	22 1/2"	34	140	1500W, 240V, 6.25A
PSST-120-3 or 3S	3	45 3/4"	22 1/2"	34	180	2250W, 120V, 18.8A
PSST-208-3 or 3S	3	45 3/4"	22 1/2"	34	180	2250W, 208V, 10.82A
PSST-240-3 or 3S	3	45 3/4"	22 1/2"	34	180	2250W, 240V, 11.9A
PSST-120-4 or 4S	4	60 1/8"	22 1/2"	34	225	3000W, 120V, 25A
PSST-208-4 or 4S	4	60 1/8"	22 1/2"	34	225	3000W, 208V, 14.42A
PSST-240-4 or 4S	4	60 1/8"	22 1/2"	34	225	3000W, 240V, 15.8A
PSST-120-5 or 5S	5	74 1/2"	22 1/2"	34	260	3750W, 120V, 31.3A
PSST-208-5 or 5S	5	74 1/2"	22 1/2"	34	260	3750W, 208V, 18.3A
PSST-240-5 or 5S	5	74 1/2"	22 1/2"	34	260	3750W, 240V, 19.8A

Receptacle configurations required for Sealed Well Food Tables.

15 AMP 125V model #	15 AMP 250V model #	20 AMP 250V model #	30 AMP 125V model #	30 AMP 250V model #	50 AMP 125V model #
NEMA 5-15 plug NEMA 6-15 plug		NEMA 6-20 plug	NEMA 5-30 plug	NEMA 6-30 plug	NEMA 5-50 plug

*APW Wyott reserves the right to modify specifications or discontinue models without incurring obligation.