BUNN°

12 Cup Automatic Coffee Brewer with 5 Warmers

ITEM#		
PROJECT		
DATE		



Features

12 Cup Automatic Coffee Brewer

- Brews 7.5 gallons (28.4 litres) of perfect coffee per hour.
- · Five separately controlled warmers.
- · All stainless steel construction.
- · Models available with faucet. Faucet kits available for existing models.
- SplashGard® funnel deflects hot liquids away from the hand.

Model RT

(5 warmers) (decanters sold separately) Dimensions: 21.2" H x 24" W x 18.5" D (53.8cm H x 61cm W x 47cm D)

For current specification sheets and other information, go to www.bunn.com.

Related Products

Easy Clear® EQ-17-TL

Product No.: 30200.1000

Dimensions:

 $12^{7}\!\!/_{16}$ " H x $2^{1}\!\!/_{2}$ " W x 3" D $31.6\ \mathsf{cm}\ \mathsf{H}\ x\ 6.35\ \mathsf{cm}\ \mathsf{W}\ x\ 7.62\ \mathsf{cm}\ \mathsf{D}$

Easy Clear® ED-17-TL

Product No.: 30201.1001 Dimensions: $8\frac{1}{4}$ " H x $2\frac{5}{16}$ " Dia.

20.95 cm H x 5.87 cm Dia.



Paper Filter Pack

Product No.: 20115.0000 Packed per case: 1,000

Dimensions: $4\frac{1}{4}$ " Base x $2\frac{3}{4}$ " Sidewall

10.8 cm Base x 6.98 cm Sidewall

Easy Pour® black decanter Product No.: 06100.0101

Quantity: 1 (also packaged in

quantities of 2, 3, 6, 12, & 24)



1GPR SS Portable Server on an RWS1 Warmer

1GPR Product No.: 12487.00013 RWS1 Product No.: 12203.0010 *Also available with side handles

or black decor.



Easy Pour® orange decanter (for decaf)
--

Product No.: 06101.0101 Quantity: 1 (also packaged in quantities of 2, 3, 6, 12, & 24)



Model	Agency Listing	
RT	(U) ustee (NSF)	
RTF	U) LISTED (NSE)	

Dimensions & Specifications


Model	Product #	Volts	Amps	Tank Heater Watts		Brewing Capacity		Shipping Weight	Cord Attached
RT	20835.0000	120/240	19.2	3500	4050	7.5 gal./hr.	9.3	42 lbs.	No
RTF (w/faucet)	20835.0004	120/240	19.2	3500	4050	7.5 gal./hr.	9.3	46 lbs.	No

Brewing capacity: based upon incoming water temp of 60°F (140°F rise) per 1/2 gallon brew time of 4 minutes.

Models listed as 120/208V or 120/240V must be connected to 208V or 240V electrical service respectively. Please refer to the installation manual.

Electrical: Model requires 3-wires plus ground service rated 120/240V (115/230, 120/208), single phase, 60 hz.

Plumbing: 20-90 psi (138-621 kPa). Machine supplied with $\frac{1}{4}$ " OD male flare fitting.



Bunn-O-Matic® Corporation - 1400 Stevenson Drive Springfield, Illinois 62703 • 800-637-8606 • 217-529-6601 • Fax 217-529-6644 • www.bunn.com

BUNN® practices continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

10/09 @ Bunn-O-Matic Corporation