



THE ABSOLUTE HIGHEST INNOVATION IN WARE WASHING

ENERGY STAR

How to wash and sanitize in a quick, efficient, economic way and fully comply with today's strict hygienic and sanitation requirements? This is the request of all chefs and bakers today; who in their every-day activity are using baking trays,

pots, pans, utensils, baskets, etc. which come into contact with food. Jet-Tech provides you an answer to this question with our Series 777 & 787 cutting-edge technology warewash equipment.

Whether you operate a bakery, hotel, supermarket, school, meat department, hospital, or laboratory, these highly productive washers will ensure a perfect kitchen ware hygiene; with their specially designed star-shaped wash

arms to effectively ensure total coverage and contribute to an impeccable cleanliness. Special baskets and accessories permit the washing of every kind of wares, that is how our **Total Clean Concept** will make your life a whole lot easier!



JET-TECH MODEL 777

Ideal for medium scale washing applications, the 777 comes equipped with a 27.5" x 27.5" (70 cm. x 70 cm.) stainless steel basket with a 33.5" (85 cm.) door opening. The basket's easy slide guides greatly reduce the effort of their movement for the operator. Three automatic programs ranging up to ten minute cycle lengths.




JET-TECH MODEL 787

Ideal for large scale washing applications, the 787 comes equipped with a 52.0" x 27.5" (132 cm. x 70 cm.) stainless steel basket with a 33.5" (85 cm.) door opening. The basket's easy slide guides greatly reduce the effort of their movement for the operator.

The 787 is very capable of washing large numbers of wares to allow the greatest flexibility of usage. Incorporating our exclusive **half-load** function; activating only one of two pumps saving valuable energy during slower periods. Three automatic programs ranging up to ten minute cycle lengths.



Wash & Rinse Arm Assembly



Deep drawn tank
The ultimate in Sanitation

Total Clean Concept

Both our 777 & 787 pot, pan and utensil washer series are equipped with deep-drawn inner tanks without welds; which fully complies with the most extreme sanitary rules. The double integrated waste filters retain the largest particles, then carried to collection baskets which are easily removed. Lastly, the internal pumps are self-draining in order to avoid any odors when the machine is shut off.

CRP

CRP is the technology developed for end-users that expect absolute perfection. The CRP rinse permits you to enjoy the consistent quality results obtained; as the rinse water's temperature will not change for the total cycle duration. The water capacity and pressure are guaranteed by a built-in booster; not directly supplied from the incoming water line; but through an intermediate holding tank with a rinsing pump also located within the machine body as standard equipment.



Low voltage soft touch control panel

Helping personnel

Our pot/pan washers will ease the tedious cleaning operations at the end of the day thanks to the Total Clean Concept. Operation is intuitive and machine control is made through a soft touch low tension electric panel with few push buttons, clear pilot lights and digital display to see the washing and rinsing temperatures. The same display also shows the self-diagnostic system's messages which control the main electric components.

Ensuring hygiene

The guarantee of a rinse always at a sanitation temperature is given by the sophisticated electronic Thermostop that doesn't permit the start of this crucial phase if the water isn't at the correct temperature. The double-walled construction and the particular washing circuit's architecture allows for extraordinary silent operation. The reduction of the consuption of water and chemicals products decreases the impact of every single cycle on the environment. We allow you to comply with HACCP requirements in an easy and economical way.

JET-TECH MODEL 777						JET-TECH MODEL 787					
Dimension WxDxH	33.5" x 33.5" x 75" (85 x 85 x 190 cm)					Dimension WxDxH	58" x 33.5" x 75" (147 x 85 x 190 cm)				
Rack Dimensions	27.55" x 27.55" (70 x 70 cm)					Rack Dimensions	52" x 27.55" (132 x 70 cm)				
Door opening	33.46" (85 cm)					Door opening	33.46" (85 cm)				
WASHING PROGRAM						WASHING PROGRAM					
TIME	WASHING	PAUSE	RINSING	TOTAL CYCLE		TIME	WASHING	PAUSE	RINSING	TOTAL CYCLE	
Program 1	141 sec	16 sec	23 sec	180 sec		Program 1	141 sec	16 sec	23 sec	180 sec	
Program 2	291 sec	16 sec	23 sec	330 sec		Program 2	291 sec	16 sec	23 sec	330 sec	
Program 3	561 sec	16 sec	23 sec	600 sec		Program 3	561 sec	16 sec	23 sec	600 sec	
TEMPERATURE						TEMPERATURE					
Tank temperature	165°F (74°C)					Tank temperature	165°F	165°F (74°C)			
Booster temperature	190°F (88°C)				Booster temperature	190°F	190°F (88°C)				
WATER						WATER					
Tank capacity	17,96 gal (68 litres)					Tank capacity	34,6 gal (131 litres)				
Booster capacity	3,17 gal (12 litres)					Booster capacity	4,49 gal (17 litres)				
Water consuption	1,60 gal (6,1 litres)					Water consuption	3,19 gal (12,1 litres)				
Fill water temp.	59°F (15°C) - 149°F (65°C)					Fill water temp.	59°F (15°C) - 149°F (65°C)				
Fill water pressure	18-40 lbs (1-3 bar)					Fill water pressure	18-40 lbs (1-3 bar)				
Fill hose connection	G 3/4" M					Fill hose connection	G 3/4" M				
Drain hose diameter	1.5" (38 mm)					Drain hose diameter	1.5" (38 mm)				
ELECTRIC						ELECTRIC					
Motor	4 H.P.				Motor	2 x 4 H.P. =8 HP TOTAL					
Voltage	208V 3 phase 60 hz.				Voltage	208V 3 phase 60 hz.					
Amperage	36A				Amperage	45A					
Tank	8000W					Tank	8000W				
Booster	8000W					Booster	8000 W				
Washing pump	3000W					Washing pump	2 x 3000W = 6000W TOTAL				
Rinsing pump	250W					Rinsing pump	2 x 250W				
TOTAL LOAD	11250W					TOTAL LOAD	14250W				
SOFTWARE SYSTEMS				STANDARD		TANDARD	OPTIONAL EQUIPMENT				
Thermostop system				Autodrain wash pump			Detergent dispenser				
Quick ready system				Stainless steel wash arms			Low level detergent sensor				
CRP system				Double walled insulated body			Rinse-aid dispensing pump				
Automatic start				Double filter drain system			Low level rinse sensor				
Cycle counter (partial and total)											

JET-TECH POT, PAN & UTENSIL WASHERS							
FEATURE	DESCRIPTION	ADVANTAGE					
Thermostop	If correct rinse temperature (176°F184°F) has not been reached, wash cycle is extended	Ensures correct rinse temperature					
Quick Ready	Enables tank filling with hot water coming from booster	Machines reaches faster working temperature					
CRP System	Ensures constant rinse pressure and temperature	Optimum rinsing results					
Automatic start	When door is closed, cycle starts automatically	Easy operation					
Cycle counter (partial and total)	Counts working cycle of the day and cumulative working cycles to the date	Useful for chemical companies and end user					
Half load function (787)	It is possible to use half machine (only model 787) having two separate washing and rinsing systems. Machine will indicate that right hand side only is working	Avoids unnecessary operating costs in case of low output requirements					

