



CSFRIP Roll-Ins

Coolscapes™ Roll-In Freezer

Project _____

Item _____

Quantity _____

CSI Section 11400

Approved _____

Date _____

CSFRIP Roll-Ins

Models

CSFR1P-S

CSFR2P-S



CSFR1P-S

Standard Features

- GreenGenius™ R290 top mount refrigeration system featuring TXV expansion valve and hot gas condensate removal
- Digital exterior temperature display with high/low temp visual alarms
- Energy saving LED interior light
- Removable side louver
- Raised ABS interior door liner
- Smart door hinge that auto closes up to 90° and stays open past 90°
- Energy efficient door gasket – removable without tools
- Door locks
- 10' cord and plug attached
- Stainless steel exterior front, sides & interior
- 115V / 60C / 1 P Standard

Options


- Three drawers in place of 1 Half Door (bottom section only)
- S/S finish door liner
- Stainless steel back
- Utility base
- Kick plate
- Laminate – front, ends, shroud
- Heat shield end – max temp 400 degrees
- Trim strips

Specifications


Refrigeration system: All components are mounted to the top cabinet ceiling, outside the food zone and are assembled as one piece and can be removed as one piece. Environmentally friendly R290 refrigerant is used. System has the capability of maintaining between -5°F and 0°F in heavy use food service operations. Refrigerant is metered using a highly responsive thermostatic expansion valve. System is controlled using an electronic temperature control, which provides improved pull down times, reducing compressor cycling and longer compressor life with lower energy consumption. Control system uses adaptive defrost to assure evaporator coil is free of ice and operating at optimum efficiency. Evaporator condensate is eliminated using an energy efficient hot gas system.

Units are completely insulated with high density foamed in place environmentally friendly, Kyoto Protocol Compliant, Non ODP (Ozone Depletion Potential), Non GWP (Global Warming Potential) polyurethane.







PLAN VIEW ALL 1
SECTION MODELS




PLAN VIEW ALL 2
SECTION MODELS



ELEVATION VIEW ALL 1
SECTION MODELS



ELEVATION VIEW ALL 2
SECTION MODELS



SIDE VIEW
ALL MODELS

CSFRIP Roll-Ins
 Coolscares™ Roll-In Freezer

Specifications									
Model	V/Hz/Ph	Amps	Volume Cu. Ft.	SHELF CAPACITY SQ. FT.	No. of Shelves	Unit H.P.	Btu/Hr System Cap	Ship Weight	Nema Plug
CSFRI1P-S	115/60/1	10	37	N/A	N/A	0.68	2194		5-15P
CSFRI2P-S	115/60/1	14.7	76.5	N/A	N/A	(2X)0.55	3936		5-20P

Delfield reserves the right to make changes to the design or specifications without prior notice.