

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project :		
Model #:		
Item #:	Qty:	
Available W/H :		
Approval :		

# Solid Dual Temperature

Reach-In Top Mount M3 Series

# Model: M3RF19-2-N

## \_\_\_ FEATURES & BENEFITS =\_\_

### ■ Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

#### Digital temperature control & monitor system

- · Keep food products safe by maintaining constant temperatures.
- · Alarms that sound when doors are not sealed shut; protect against food spoilage that originates from cold air leaks.
- Early warning alarm program detects issues before malfunction occurs.
- · Digital display allows for easy monitoring.
- Programs interpret the condition of refrigeration systems by self-diagnosis.
- Rapid cool-down function (Turbo freeze).
- · Smart defrost system will defrost as needed.
- · Automatic evaporator fan motor delays.

#### ■ Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydro- carbon refrigerators designed to meet the new standards of the EPA and DOE in 2017. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

#### Hot gas condensate system

Through Turbo Air's creative innovation, the condensate system surfaces have been specially treated to resist corrosion. This not only increases efficiency without the risk of refrigerant leakage from corrosion, but also thoroughly prevents the overflow of condensate water.

#### ■ Exterior & interior of cabinet construction

Stainless steel exterior (galvanized steel top, bottom and back) and AL interior with stainless steel floor. It guarantees the utmost in cleanliness and long product life. Unlike other companies' products, sharp corners and edges have been rounded to reduce the risk of injury.

- Adjustable, heavy duty, PE (polyethylene) coated wire shelves
- Left hinged model available (M3RF19-2-N-L)
- LED interior lighting

### ■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

■ Refrigerator holds 33°F ~ 38°F, and freezer holds -10°F ~ 0°F for the best in food preservation



#### Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.













M3RF19-2-N	2	8.39(F) 8.87(R)	2	3/8	4.8	220	251/8 x 311/2 x 72
Model	Swing Door	CU./FT.	#of Shelves	НР	AMPS	Crated Weight (lbs.)	L x D*x H† (inches)

# Solid Dual Temperature

# **Model: M3RF19-2-N**

ELECTRICAL DATA	ECTRICAL DATA			
Voltage	115/60/1			
Plug Type	① NEMA 5-15P			
Full Load Amperes	4.8			
Compressor HP	3/8			
Feed Wires with Ground	3			
Cord Length (ft.)	9			
Refrigerant	R-290			
DIMENSIONAL DATA				
# of Doors	2			
Net Capacity (cu. ft.)	8.39(F) / 8.87(R)			
Ext. Length Overall (in.)	251/8 (640mm)			
Ext. Depth Overall (in.) *	311/2 (800mm)			
Ext. Height Overall (in.)†	72 (1830mm)			
Freezer Int. Dimension (L x D x H) (in.)	215/8 x 273/8 x 257/4			
Ref. Int. Dimension (L x D x H) (in.)	215/8 x 255/8 x 285/8			
Gross Weight (lbs.)	220			
# of Shelves	2 201/2 x 233/4			
Shelf Size (in.)				

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

\* Depth does not include 2-1/2" for rear condensate enclosure.

#### 3 Year Parts and Labor Warranty Additional 2 Year Warranty on Compressor


- Anti-corrosion coated evaporator
- Door locks standard
- Self-contained system
- Standard 4" dia. swivel casters with locks on the front set
- Solid and sturdy grille design
- Legs available (optional)


### ■ OPTIONAL ACCESSORIES:

- ☐ 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- ☐ 6" stainless steel leg: 30221M0600
- ☐ Additional PE coated wire shelf: K1F9000103

## **PLAN VIEW**







Ver.20180312
















■ Warranty: 800-381-7770 ■ AC: 888-900-1002











<sup>†</sup> Height does not include 5" for caster height.