



## PRO CART ULTRA™ (HOT, COLD AND/OR PASSIVE)

The first holding cabinet and transport cart to actively hold both hot and cold food at the same time—without a compressor.

- High capacity cart holds GN food pans, sheet pans, trays and pizza boxes in two separate, insulated cabinets.
- Customize the cart to suit your menu with a choice of active hot, active cold or passive holding in each cabinet.
- Energy efficient, active modules draw less than 5 amps each.
- Cold module uses environmentally-friendly, thermoelectric technology.
- Active modules also sold separately to quickly adapt to menu or operational changes.
- Even without electricity, this cart can maintain safe temperatures for 4+ hours.
- Comes standard with upgraded, 6" heavy duty casters.
- 110V and 220V available.

**Color:** Charcoal Gray (615).

Multiple International Certifications available.




# PRO CART ULTRA™ (ELECTRIC HOT AND COLD)



## ELECTRIC HOT

Keeps food safely between 150° to 165°F with convenient, pre-set, gentle, nonradiant heat.



## ENERGY-SAVING HEATER over 50% more


energy efficient compared to leading metal carts! Gentle, non-radiant heat circulates consistently from front to back of the cabinet.



Tall Cart

## ELECTRIC COLD

Digital controller allows cold to be set from 32.5° to 40°F.



## THERMOELECTRIC COOLING cools down to 32.5°F

without a compressor for the ultimate in cold mobility and food safety on the go.

**Note:** Operate in 90°F or less environments for best results.



Interior with Hot module



Interior with Cold module



Exterior back with Hot module



Exterior back with Cold module



Low Cart

Pre-heat time: 45 minutes.  
Recovery time: 3 minutes after door open for 30 seconds.

Pre-chill time: 90 minutes to 40°F. (Tested at 73°F ambient.)  
Recovery time: 10 minutes after door open for 30 seconds.

# PRO CART ULTRA™ (ELECTRIC HOT AND COLD)



Holds Combinations of GN Food Pans, Sheet Pans, Trays and Pizza Boxes to suit your need.



## Holding Capacity Reference



TYPE OF CONTAINER	TALL CART STANDARD CAPACITY	LOW CART STANDARD CAPACITY	TALL CART MAXIMUM CAPACITY	LOW CART MAXIMUM CAPACITY
18" x 26" FULL SIZE SHEET PANS	16	8	32*	16*
13" x 18" HALF SIZE SHEET PANS	32	16	64*	32*
GN 1/1 FOOD PANS 2½" DEEP	32	16	32	16
GN 1/1 FOOD PANS 4" DEEP	20*	10*	20	10
15¾" x 23¾" SHEET PANS**	16	8	32*	16*
PIZZA BOXES 16" x 16" x 2"	16	8	16	8

\*Additional rails required. \*\*Pans for European Market.



Easy to change modules add flexibility to any operation.

# PRO CART ULTRA™ (ELECTRIC HOT AND COLD)




**INSULATION**  
CFC-free, polyurethane insulation throughout the body and doors maximizes heat or cold retention for 4 hours or more with no electricity needed.

**New!**

**MARINE RAIL**  
Creates a bonus staging area for food pans.

**GASKET-FREE DOOR**  
For easy cleaning and fewer replacement parts. Door opens full 270°.



**SOLAR DIGITAL THERMOMETER**  
Monitor internal cabinet temperature at a glance.

**MAGNETIC QUICK CLOSE FEATURE**  
Helps the operator close the door with little effort — especially helpful when hands are full.

**4" NYLON LATCHES AND ADJUSTABLE HINGES**  
For easy opening and closing and to secure contents during transport. (Door is lockable).

**5" x 8" MENU POCKET**  
Allows for easy product ID with either an index card or by writing directly onto smooth surface with a grease pencil.



**STANDARD 6" x 2" HEAVY DUTY CASTERS**  
Two non-marking, high-performance, all swivel casters with brakes in the front and two rigid casters in the back for smooth positioning and navigation.

**PERIMETER BUMPER**  
Protects cart and walls.



**STAINLESS STEEL HINGE**  
for long term durability.

**POLYETHYLENE EXTERIOR**  
Keeps food moist naturally and remains cool to the touch during operation, unlike metal cabinets.

**Color:** Charcoal Gray (615).

Multiple International Certifications available.



## Ergonomic Molded-In Handles

Will never break; great for maneuvering by operators of all heights.



## Cord Keeper

Stores 9' power cord neatly and safely.



## 8 Sets of Stainless Steel Universal Rails



With 1.5" spacing; hold sheet pans, food pans, pizza boxes and trays (or a combination).



## Rail Guides

Numbering corresponding to different holding containers helps speed set-up.

# PRO CART ULTRA™ (ELECTRIC HOT AND COLD)

	CODE	DESCRIPTION	UNIT WEIGHT	LIST PRICE EA.
<b>TALL PROFILE</b> 	<b>Both Compartments Hot</b>			
	PCUHH	110V standard USA / CAN power cord 5-15P	267.5 lbs.	\$ 8,060.00
	PCUHH2	220V USA / CAN power cord 6-15P	268.4	8,060.00
	<b>Both Compartments Cold</b>			
	PCUCC	110V standard USA / CAN power cord 5-15P	278.4	12,585.00
	PCUCC2	220V USA / CAN power cord 6-15P	283.8	12,585.00
	<b>Hot &amp; Cold</b>			
	PCUHC	Top compartment hot, bottom cold. 110V standard USA / CAN power cord 5-15P	271	11,440.00
	PCUCH	Top compartment cold, bottom hot. 110V standard USA / CAN power cord 5-15P	271	11,440.00
	PCUHC2	Top compartment hot, bottom cold. 220V standard USA / CAN power cord 6-15P	271.4	11,440.00
	PCUCH2	Top compartment cold, bottom hot. 220V standard USA / CAN power cord 6-15P	271.4	11,440.00
	<b>Passive &amp; Hot or Cold</b>			
	PCUPH	Top compartment passive, bottom hot. 110V standard USA / CAN power cord 5-15P	255.3	7,260.00
	PCUPC	Top compartment passive, bottom cold. 110V standard USA / CAN power cord 5-15P	260.8	8,405.00
PCUPH2	Top compartment passive, bottom hot. 220V standard USA / CAN power cord 6-15P	255.8	7,260.00	
PCUPC2	Top compartment passive, bottom cold. 220V standard USA / CAN power cord 6-15P	263.5	8,405.00	
<b>LOW PROFILE</b> 	PCULH	Hot Cart, 110V standard USA / CAN power cord 5-15P	151	5,200.00
	PCULC	Cold Cart, 110V standard USA / CAN power cord 5-15P	156	7,200.00
	PCULH2	Hot Cart, 220V standard USA / CAN power cord 6-15P	151	5,200.00
	PCULC2	Cold Cart, 220V standard USA / CAN power cord 6-15P	156	7,200.00

**Case Pack:** 1 **Color:** Charcoal Gray (615).

**Standard Railing Includes:** 8 pairs of stainless steel Universal rails/compartment.

**Includes Standard Casters:** 6" x 2" heavy duty swivel with brake in front, rigid in back.

**Options:** Security Package (S) available by special request.

## Unit Dimensions

UNIT	EXTERIOR DIM. W x D x H	COMPARTMENT DIM. W x D x H
<b>Tall Profile</b>		
COLD	28" x 36½" x 66"	21½" x 26¼" x 25½"
HOT / PASSIVE	28" x 35¾" x 66"	21½" x 27" x 25½"
<b>Low Profile</b>		
COLD	28" x 36½" x 40"	21½" x 26¼" x 25½"
HOT / PASSIVE	28" x 35¾" x 40"	21½" x 27" x 25½"

## Electrical Specifications (Per Compartment)

	HOT 110V	HOT 220V	COLD
REQUIRED VOLTAGE	100-125 VAC	200-230 VAC	100-230 VAC
MAXIMUM AMP	4.6a	2.3a	3.26a, 1.42a
WATTS / HEATER OR COOLER	529w	506w	326.6w
HERTZ	50/60	50/60	50/60
PHASE	Single	Single	Single
ALTERNATE PLUG TYPES FOR INTERNATIONAL*	US, Canada, Mexico, Europe, UK, Ireland, Australia, South Africa, China, Japan		
POWER CORD LENGTH	9 ft.	9 ft.	9 ft.

\*If country is not listed, please call Cambro Customer Service for details.

## Optional Accessories

CODE	DESCRIPTION	LIST PRICE EACH
PCMH / PCMH2	Hot module unit 110V / 220V	\$ 1,622.00
PCMC / PCMC2	Cold module unit 110V / 220V	2,766.00
SSR1	1 Pair of Rails	82.00
SSR8	8 Pairs of Rails	595.00

**Case Pack:** 1 **Color:** (000).

