

ELEVATION SERIES CUBE ICE MAKER CIM1126/1125



Model:

CIM1126CIM1125



CIM1126 ON B42


Features and Benefits

- 22.25" (565 mm) wide space-saving design.
- Produces up to 1,035 lbs (439 kg) of ice per day.
- Energy and Environment
 - Exceeds new 2018 DOE (Department of Energy) regulations.
 - Up to 20% more energy efficient than other models.
 - Environmentally friendly, including BPA-free plastic and recyclable parts.

Sanitation

- Plastic Food Zone eliminates hard-to-clean nooks and crannies, allowing for effortless wipe down and easy, long-lasting sanitation.
- Built in Agion[®] ensures unbeatable antimicrobial protection.
- Smart LED light indicates machine status and when cleaning is required.
- Simple, one-touch controls for sanitization and descaling.
- BPA-free snap-in, snap-out dishwasher-safe components.
- Universal Smart Harness[™] control board simplifies installation and servicing with better access, digital diagnostics, universal components and common configuration.

Ice Form



CUBE



	ICE STORAGE BINS											
Kits	Model No. Capacity Width	B25 242 lbs (110 kg) 30 in (762 mm)	B40 344 lbs (156 kg) 30 in (762 mm)	B42 351 lbs (160 kg) 22 in (559 mm)	B55 510 lbs (232 kg) 30 in (762 mm)	B700 680 lbs (308 kg) 30 in (762 mm)	B110 854 lbs (388 kg) 48 in (1,219 mm)	B1000 1,000 lbs (454 kg) 48 in (1,219 mm)	B1300 1,320 lbs (599 kg) 48 in (1,219 mm)	B1325 1,325 lbs (601 kg) 60 in (1,524 mm)	B1660 1,660 lbs (753 kg) 60 in (1524 mm)	
	CIM1126	KBT19		Kit Not	KBT19		KBT23C	Hold Down Securement				
	CIM1125			Required	ND	113	19 KD123C	Recommended				

*See Ice-O-Matic Price List for Adapter Kits to combine ice makers with most available ice/beverage dispensers.

Options & Accessories

WATER FILTERS							
Ice Machine Model	Manifold						
	System	Replacement					
CIM1126	IFQ2	IOMQ (2)					
CIM1125	IFQZ	101MQ (2)					

Note: All modular cube CIM units can be installed with manufacturer approved ozone delivery systems.

Ice Maker Warranty

COMMERCIAL WARRANTY						
Ice Maker	3 YEARS parts and labor					
Evaporator and Compressor	5 YEARS parts					
Evaporator (when enrolled in our filter program)	7 YEARS parts and labor					



CIM1126/1125



_1.6" (41mm) (2x)

D.

17.0" (432mm)

Α.

6.5'

-В.

(166mm)

2.1" (53mm)

> -1.0" (25mm)


-1.1" (28mm) (2x)


C

e ©

ē

3.0" (76mm) 18.2" (463mm)





Air Cooled

Please note: air-cooled units require 6" (152 mm) clearance for air intake and exhaust.

- A. Ice maker potable water in, 3/8" FPT.
- B. Ice maker water out, 3⁄4" FPT.
- C. Hole for electrical connections, 7/8".
- D. Electrical connection junction box, 7/8".

Remote Cooled

5.7" (144mm)

1.8"

(45mm)

A. Ice maker potable water in, 3/8" FPT.

Ε.

F.

.3"_ (4x) (8mm)

1.0" (25mm)

3.0" (76mm)

3.2" (80mm)

4.0" (102mm)

- B. Ice maker water out, 3/4" FPT.
- C. Hole for electrical connections, 7/8".
- D. Electrical connection junction box, 7/8" (remote).
- E. Condenser water in, ³/₈" FPT (water only). Discharge line, ¹/₂" male quick connect coupling for precharged line set (remote only).

G.

- F. Condenser water out, 1/2" FPT (water only).
- G. Liquid line, ³/8" male quick connect for precharged line set (remote only).

Operating Requirements

	MINIMUM	MAXI	MUM	
		60 Hz	50Hz	
Ambient Temp. Range Air	50°F (10°C)	100°F (38°C)	110°F (43°C)	
Water Temp.	40°F (4.4°C)	100 1 (30 C)		
Water Pressure	20 PSIG (1.4 BAR)	80 PSIG (5.5 BAR)		

Dimensions

Remote Cooled

B 7

ALL MODELS							
W x D x H (in.)	22.25 x 24.25 x 26.9						
W x D x H (mm)	565 x 616 x 683						

Specifications

		Ice Pro	Cube duction 24hrs	gallons per 1	Usage 00 lbs of Ice 70°F water	kWH Used					
Model Number	Cond. Unit	70°F air/ 50°F water Ibs (kg)	90°F air/ 70°F water Ibs (kg)	Potable	Condenser	per 100 lbs of ice @ 90°F air/ 70°F water	Voltage Characteristics	Min. Circuit Ampacity	Min/Max Circuit Breaker	Approx. BTUs per hour	
CIM1126A	Air	932 (423)	762 (346)	19.0	N/A	5.1		12.2			
CIM1126R**	Remote	968 (439)	855 (388)		19.0	N/A	5.0	208-230/60/1	12.8		18,200
CIM1126W	Water	968 (439)	896 (406)		140.0	4.1		11.8	20/25		
CIM1125A	Air	950 (431)	790 (358)	18.0	N/A	5.1		13.5		10 700	
CIM1125R**	Remote	1035 (469)	927 (420)		10.0	10.0	ту/А	4.6	220-240/50/1	14.1	

* Daily ice production based on half cube configuration. When installing a CIM on a drink dispenser, the KCUBEDISPB MUST be used.

** Remote models CIM1126R & CIM1125R require the RCA-2061 remote condenser with optional grill guard kit.

 Notes:
 3 (including ground)

 Number of Wires:
 3 (including ground)

 Approx. Shipping Weight Ibs (kg):
 CIM1126A 230 (105) • CIM1126R 215 (98) • CIM1125A 230 (105) • CIM1125R 215 (98)

 Refrigerant Type:
 CIM1125A = R449A