




STAINLESS STEEL
Uni-Serv Speed Bars NSF
26" Wide



CRU-60R Shown

Item #: _____ Qty #: _____
 Model #: _____
 Project #: _____



15A - 120V Duplex
 Receptacle Hidden
 Beneath Blender Shelf



FEATURES:

- 30" x 15" x 12" insulated ice bin; 98 lbs. ice capacity.
- 10"W x 14"L x 10"D dump sink.
- Recessed drainboard for glassware storage.
- Dual blender/mixer recessed station with 15A - 150V duplex outlet hidden beneath shelf.
- Includes two removable plastic bottle racks.
- Galvanized legs with adjustable plastic bullet feet.
- Adjustable galvanized side cross-bracing.
- 4" backsplash.
- Optional 7-circuit cold plate sealed into the bottom of the ice bin.

MECHANICAL:

- Includes K-52 splash mount gooseneck spout faucet.
- Faucet meet federal lead free standards.**
- 1" IPS drains (sink bowl, recessed drainboard and ice bin).
- 15 amp. - 120V duplex receptacle.

MATERIAL:

- 22 gauge, 300 stainless steel
- Sink Bowl:** 20 gauge, 300 stainless steel
- Understructure:** 22 gauge galvaneal front/back; 11 gauge electrogalvaneal leg channel
- Legs:** 1 5/8" O.D. 18 gauge, galvanized steel with adjustable plastic bullet feet
- Ice Bin Insulation:** 2 lbs. density styrofoam (non-cold plate models); 2 lbs. density foam-in-place (cold plate models)
- Cold Plate:** Cast aluminum with 7 circuits (5 syrup and 2 water lines) with 5/16" diameter stainless steel bump and swedge ends.

OPTIONAL:

- K-316-LU** - Add wrist handles
- SU-10A** - 18" stainless steel leg upgrade with cross-bracing
- SU-10C** - 14" stainless steel leg upgrade with cross-bracing

Model #	Overall Length	Ice Bin Capacity	Ice Bin Location	Approx. Weight	Approx. Cu. Ft.
CRU-60L	60"	98 lbs.	Left	110 lbs.	23
CRU-60R	60"	98 lbs.	Right	110 lbs.	23

With 7-Circuit Cold Plate

CRU-60L-7	60"	98 lbs.	Left	193 lbs.	23
CRU-60R-7	60"	98 lbs.	Right	193 lbs.	23

L And R Indicate Ice Bin Location.



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 8:00 pm E.S.T.

For Orders & Customer Service:
 Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Quotes:
 Email: smartfab@advancetabco.com or Fax: 631-586-2933

DIMENSIONS and SPECIFICATIONS

TOL Overall: ± .500" Interior: ± .250"

ALL DIMENSIONS ARE TYPICAL

CRU-60L-7 Series Shown (With Cold Plate)

