



The Signature of Quality

FEDERAL INDUSTRIES

A Standex Company
215 Federal Avenue
Belleville, WI 53508-9201

Phone: 800-356-4206
Fax: 608-424-3234
Email: geninfo@federalind.com
Website: www.federalind.com

Project Name: _____

Item #: _____

Model #: _____ Qty: _____

Approval: _____

AIA#

SIS#

SQ MARKET DELI™ REFRIGERATED CORNER CASES SERVICE & SELF-SERVE

Market Deli. The low-profile merchandiser that provides solutions to your fresh food merchandising needs. Corner Cases are available in 45° and 90°, inside and outside, service and self-serve. Designed for continuous case line-ups without middle end glass.



MODEL	DIMENSIONS (Includes End Panels)
<input type="checkbox"/> SQROC90	47.75 x 71.50 x 48 (in) 1213 x 1816 x 1219 (mm)
<input type="checkbox"/> SQROC90SS	47.75 x 71.50 x 32-1/4 (in) 1213 x 1816 x 819 (mm)
<input type="checkbox"/> SQRIC90	53.75 x 90-1/4 x 48 (in) 1365 x 2292 x 1219 (mm)
<input type="checkbox"/> SQRIC90SS	53.50 x 90.25 x 32-1/4 (in) 1359 x 2292 x 819 (mm)
<input type="checkbox"/> SQROC45R	50.25 x 41.50 x 48 (in) 1276 x 1054 x 1219 (mm)
<input type="checkbox"/> SQROC45SSR	50.25 x 41.50 x 32-1/4 (in) 1276 x 1054 x 819 (mm)
<input type="checkbox"/> SQRIC45	53.50 x 57 x 48 (in) 1359 x 1448 x 1219 (mm)
<input type="checkbox"/> SQRIC45SS	53 x 57 x 32.25 (in) 1346 x 1448 x 819 (mm)

STANDARD FEATURES

Model Features

- Lift-up pneumatic, cylinder-assisted curved front glass.
- Adjustable Leg Levelers
- Rear work counter.
- Pedestal or panel base design.
- Tempered front and end glass.
- Stainless steel interior and exterior finish.
- Solid-state controls.
- Designed for continuous line-ups.

Lighting

- LED case lighting.

Refrigeration

- Condensate evaporator provided on self-contained systems. Remote refrigeration available.
- Average case temperature of 36° to 38° F is maintained.
- Oversized coil and low-velocity fan system maintains product freshness and high humidity.
- Coated evaporator coil.
- Thermometer
- R513a Refrigerant (R449a in Remote Applications)

Agency Approvals

- UL Safety and UL Sanitation listed
- DOE 2017 Compliant.

OPTIONAL ACCESSORIES

- Special Case Height (50" or 52")
- Front Bumper Rail
(Black, White, Green, Gray)
- Reflective End Glass
(Service Case Only)
- Remote Refrigeration (EEV Included)
- Scale Stand
- Top Service Shelf
(Service Case Only)
- Humidity Control
(Service Case Only)
- Accent Base Light
- Slicer Stand
- Non Glare Glass
- Mezzanine Shelf, Lighted
(For Non-Refrigerated Product
– Service Case Only)
- Cord & Plug



WARRANTY*
One year Parts and Labor
2nd thru 5th year part
only service compressor
(U.S.A and Canada)

Note: Information is subject to change at any time.
Visit www.federalind.com for the most current specs.

Revised 01/18/2020

AIA#

SQ MARKET DELI™ REFRIGERATED CORNER CASES SERVICE & SELF-SERVE

SIS#







Product Specifications

Intended Environment: Type I - Designed to operate in maximum ambient conditions of 75°F (24°C) and 55% relative humidity unless noted otherwise in system information below.





Zone	Intended Product To Be Displayed	Avg Prod Temp °F/°C
All	Packaged Refrigerated Products	38°F / (3.3°C)

DIMENSION: xx"/(mm)

DIMENSION TOLERANCE +/- 0.25 (6.4)



MODEL	* DIMENSIONS				SELF CONTAINED 120/60/1	*REMOTE 120/60/1
	L	D	H1	UNITS		
SQROC90	47.75	71.50	48	in.	1/2 HP - 11.5 AMPS	6 AMPS
	1213	1816	1219	mm.		
SQROC90SS	47.75	71.50	32.25	in.	1/2 HP - 11.5 AMPS	6 AMPS
	1213	1816	819	mm.		
SQRIC90	53.75	90.25	48	in.	1/2 HP - 13.8 AMPS	7 AMPS
	1365	2292	1219	mm.		
SQRIC90SS	53.5	90.25	32.25	in.	1/2 HP - 13.8 AMPS	7 AMPS
	1359	2292	819	mm.		
SQROC45R	50.25	41.50	48	in.	-	6 AMPS
	1276	1054	1219	mm.		
SQROC45SSR	50.25	41.50	32.25	in.	-	6 AMPS
	1276	1054	819	mm.		
SQRIC45	53.5	57	48	in.	1/2 HP - 11.5 AMPS	6 AMPS
	1359	1448	1219	mm.		
SQRIC45SS	53	57	32.25	in.	1/2 HP - 11.5 AMPS	6 AMPS
	1346	1448	819	mm.		



- * Without decorative end panel.
- Outside 45° corners available as remote models only.
- **When ordering, specify case line-up and pedestal or panel design**
- If a GFCI circuit is required, a GFCI Breaker MUST be used instead of GFCI receptacle.
- Refrigerated cases are designed to operate in a maximum of 75°F (24°C) ambient and 55% relative humidity.
- Due to continuing engineering improvements, specifications are subject to change without notice.



FEDERAL INDUSTRIES
A Standex Company
215 Federal Avenue Belleville, Wisconsin 53508-9201

Phone: 800-356-4206
Fax: 608-424-3234
Email: Geninfo@Federalind.com
Website: Federalind.com