



The U3 pump is the simplest pump available. No disassembly required for cleaning. The U3 pump has a capacity of 38 gallons per hour of standard soft serve or shake mix with an adjustable overrun. For use with all remote soft serve and shake freezers.

Dimensions: 10-1/2"D x 9-3/4"W x 8-1/2"H,
weight: 27 lbs.

Electrical: 1 phase, 115 VAC, 60Hz.
1.6 running amps;
Cord and plug attached.

International Option: 1 phase, 220-240 VAC, 50Hz

Warranty: One year parts only.
Excludes wear items and labor.

Includes: Spare parts kit, wall mounting bracket, and suction tubing.

Continuous research leads to ongoing product improvements; therefore, these specifications are subject to change without notice.


Distributed by:



502 Hwy. 67 Kiel, WI 53042-1600
920-894-2293 • 800-558-5807
Fax: 920-894-7029
E-mail: foodservice@stoelting.com
www.stoeltingfoodservice.com

ISO 9001:2000 Registered

Certified, Listed, and/or Recognized by:





The 219 pump has a capacity of 45 gallons per hour of standard soft serve or shake mix with an adjustable overrun. For use with all Stoelting manufactured freezers. Includes a built-in pressure relief valve to prevent excessive pressure build-up in the freezing cylinder or mix line, and air-controlled pressure switch and overload protection. Factory set pressure.

Dimensions: 8-3/4"D x 15"W x 17-1/2"H;
weight: 33 lbs.

Electrical: 1 phase, 115 VAC, 60 Hz.,
0.7 running amps;
Cord and plug attached.

Warranty: One year parts only.
Excludes wear items and labor.

Includes: Spare parts kit, wall mounting
bracket, and suction tubing.

Continuous research leads to ongoing product improvements, therefore, these specifications are subject to change without notice.

Distributed by:



502 Highway 67 • Kiel, WI 53042-1600
920-894-2293 • 800-558-5807
Fax: 920-894-7029
E-mail: foodservice@stoelting.com
www.stoeltingfoodservice.com

ISO 9001:2000 Registered

Certified, Listed and/or Recognized by:

