



Project _____
 Item # _____ Quantity _____
 Model # _____



**Countertop, Portable, Sizzle
 Induction Range**

(Model Shown: SM-351C-FT)

Model #	Voltage	Peak Power	Plug Type
SM-351C-FT (US)	208-240	3500 W	NEMA 6-20P
SM-353C-FT (Int'l)	220-240	3500 W	CEE-7/7 16A Schuko
SM-353C-FTU (UK)	220-240	3000 W	BS 1363 (13A) U.K.

Description:

Spring USA's Countertop, Portable, *Sizzle* Induction Range is a heating unit for product cooking or holding. The range features a durable, titanium colored stainless steel body and integrated oversized pan support. Each range includes our exclusive SmartScan® technology with over/under voltage protection, pan size and pan type recognition, and large LED power/temp display.

Construction & Performance Features:

- Tempered, black, smoked glass faceplate
- Rugged, 5 mm thick, easy to clean, tempered glass top
- 100% silicone rubber protective top seal
- Non-skid, non-scratch footing/base
- 7' power cord with plug
- Removable mesh air filter
- Simple, solid state controls
- Power ON/OFF touch control with pre-set timer settings

- Power ON/Pan-Present indicator lights
- Timer countdown: 30, 45, 70 & 80 seconds
- Lighted time indicator
- Cycle complete 'beep' at timer countdown

Standard Warranty:

Spring USA *Sizzle* Induction Ranges offer a three (3) year, overnight exchange warranty, from the date of invoice, against manufacturers defects. See SpringUSA.com for more details.

Agency Listings:

- ETL
- UL STD 197
- FCC
- CETL
- ETL-Sanitation to NSF-4



Countertop, Portable, Sizzle Induction Range


Available Accessories/Alternate Configurations:

- Storage & Transport Box [Spring USA Catalog]
- Induction-ready Cookware and Serving Vessels [Spring USA Catalog]
- AF-350 Under-Counter Air Filter System
- Built-In, High Power Induction Ranges
- Custom Tabletop Induction featuring SmartStone®
- Cooking Utensils [Spring USA Catalog]

Electric Requirements:

Model #	Voltage	Phase	Hertz	Watts	Amps	Plug
SM-351C-FT (US)	208-240	1	60	3500	14.6	NEMA 6-20P
SM-353C-FT (Int'l)	220-240	1	50-60	3500	14.6	CEE-7/7 16A Schuko
SM-353C-FTU (UK)	220-240	1	50-60	3000	12.5	BS 1363 (13A) U.K.

Key Dimensions:



Net Weight: 18.0 lb. (8.2 kg)



Project _____

Item # _____ Quantity _____

Model # _____

Countertop, Portable, *Sizzle* Induction Range

Shipping Dimensions:

Single Unit Shipping Carton

Model #	Length	Width	Height	Weight
SM-351C-FT (US)	25.0"	18.0"	7.9"	25.0 lb.
SM-353C-FT (Int'l)	635 mm	457 mm	201 mm	11.3 kg
SM-353C-FTU (UK)	635 mm	457 mm	201 mm	11.3 kg

Notes & Conditions:

1. For optimum performance, allow 4" clearance from front and sides for good air circulation.
Proper ventilation must be provided at all times.
2. Actual range temperature may vary due to a number of variables, such as ambient temperature in the immediate surrounding area, content and volume of food being heated or cooked, and whether or not you are using a cover on the serving vessel.
3. This induction range requires use of ferrous metal, induction-ready cookware.
4. Spring USA Induction Servers and Induction Warmers/Ranges are designed to work together as a system. Optimal performance is achieved by using Spring USA components in conjunction with each other. As the first to offer such induction systems, Spring USA cannot warranty the performance of facsimile products offered by other companies.