



ULTIMATE RESTAURANT RANGE 36" SERIES

Standard Features

- Commercial gas range 36" wide with a 37" high cooking top
- 4" Stainless steel front rail, stainless steel front and sides
- Front located manual gas shut-off to entire range
- One year No Quibble, 24/7 parts and labor warranty
- Factory installed Regulator
- Cast iron grate top will hold a 14" stock pot
- Standing pilot for open top burners
- Battery spark ignition for oven bases

Optional 33K Non-clog Burners (Burner Option 1)

- (6) patented, one piece, lifetime clog free, cast iron burners
- 33,000 BTU NAT

Optional Wavy Grates (Burner Option 2)

- Cast bowl design for better efficiency
- Allows full use of entire range top
- Available only with 27K BTU Non-clog burners

Optional Cast Iron Star/Saute' Burners (Burner Option 3)

- (6) 33,000 BTU NAT star burners
- Port arrangement allows for even distribution of flame

Optional Split Burner Configuration (Burner Option 4)

- (3) Star/Saute' burners in front and (3) standard 33K burners in rear

Optional 5 Burner Configuration (Burner Options 5 and 6)

- Combine (2) Pyromax burners in the rear with either (3) standard 33K burners (Opt 5) or (3) star 33K burners (Opt 6) in the front

Optional Pyromax Burners (Burner Option 7)

- 40,000 BTU NAT
- PATENTED high output, three piece, easy clean Non-clog burner
- Built in port protection drip ring
- Group of 4 burners available

Optional Griddle Top (L or R)

- 12", 24" or 36" Available
- 1/2" thick cold rolled steel griddle plate
- Manual or thermostatically controlled

Optional Charbroiler (L or R)

- 24" or 36" Available
- Removable, cast iron grates

Configure your own custom spec sheet
and model number at
www.BuildMyRange.com.
Refer to AutoQuotes for list pricing.



(4361D Shown)



Job _____
Item# _____

CONSTRUCTION SPECIFICATIONS

Exterior Finish: Stainless steel front, sides and shelf standard.

RangeTop: 27" deep cooking surface. Center-to-center measurements between burners not less than 12", side-to-side or front-to-back. A removable one piece drip tray is provided under burners to catch grease drippings.

Flue Riser: 22.5" flue riser standard with heavy duty shelf. Optional 10" and 5" flue riser available without shelf.

Oven Door: Spring assisted, counterweight door.

Oven Interior: Double sided, full porcelain enamel oven cavity for superior cleanability and corrosion protection. Covered corners for easy cleaning and enhanced airflow eliminating hot/cold spots.

Legs: 6" stainless steel adjustable legs standard (casters optional)

Pressure Regulator: Factory installed.

Available Base Combinations

D, A, C, HxxxxD, HxxxxA

Standard Oven Models (D)

45,000 BTU NAT oven with standing pilot and thermostat range of 175°F to 550°F (79°C to 288°C). Porcelain enamel interior measuring 14" high x 26" wide x 26.5" deep. Full sized pans fit both ways. One rack with two position side rails.

Convection Oven Models (A):

32,000 BTU NAT convection oven with standing pilot and thermostat range of 175°F to 550°F (79°C to 288°C). Porcelain enamel interior measuring 14" high x 26" wide x 24" deep. Three racks with five position side rails. 1/2 hp, 1710 rpm, 60 cycle, 115V AC, high efficiency, permanent split phase motor with permanent lubricated ball bearings, overload protection and Class "B" insulation. On/Off switch to allow CO base to operate as a standard oven.

Stainless Steel Cabinet (C)

Stainless steel cabinet base. Optional no-charge doors that open from the center.

Hybrid Electric Standard Oven (HxxxxD)


4.5 kW electrically heated oven, with all the same base features of the gas standard oven at left (D).

Hybrid Electric Convection Oven (HxxxxA)

6 kW electrically heated oven, with all the same base features of the gas standard oven above (A).



Dimensions -in (mm)



| MODELS | EXTERIOR | | | | | | | | | | | COOK TOP | DOOR OPENING | OVEN BOTTOM | 3/4" GAS CONN. | | ELECTRIC | |
|---------------|-----------------|------------------|-----------------|-----------------|-----------------|---------------|------------------|-----------------|-----------------|----------------|----------------|-----------------|-----------------|-----------------|----------------|-----------------|-----------------|----------------|
| | WIDTH A | DEPTH B | C | D | E | F | G | H | J | K | L | | | | M | N | O | P* |
| 436_D, H436_D | 36.50" (927) | 34.00" (864) | 29.75" (756) | 31.00" (787) | 10.00" (254) | 2.75" (70) | 59.50" (1511) | 22.50" (572) | 31.00" (787) | 6.00" (152) | - | 37.00" (940) | 15.50" (394) | 13.00" (330) | 3.25" (83) | 30.25" (768) | - | - |
| 436_A, H436_A | 36.50" (927) | 42.13" (1070) | 29.75" (756) | 31.00" (787) | 10.00" (254) | 2.75" (70) | 59.50" (1511) | 22.50" (572) | 31.00" (787) | 6.00" (152) | 8.25" (210) | 37.00" (940) | 15.50" (394) | 13.00" (330) | 3.25" (83) | 30.25" (768) | 24.00" (610) | 6.00" (152) |

| MODELS | OVEN INTERIOR | | | CRATE SIZE | | | CUBIC VOLUME | CRATED WEIGHT |
|---------------|-----------------|-----------------|-----------------|------------------|------------------|------------------|--------------------------|---------------------|
| | WIDTH | DEPTH | HEIGHT | WIDTH | DEPTH | HEIGHT | | |
| 436_D, H436_D | 26.00" (660) | 26.50" (673) | 14.00" (356) | 58.00" (1473) | 48.00" (1219) | 44.00" (1118) | 70.9 cu. ft 2.01cu.m. | 660 lbs. 300 kg. |
| 436_A, H436_A | 26.00" (660) | 24.00" (610) | 14.00" (356) | | | | | |

*Gas Connection will be located on opposite side of optional griddle/charbroiler location (if optional griddle/charbroiler is located on the left, the gas connection will be moved to the right side).
 Configure your own custom spec sheet and model number at www.BuildMyRange.com.
 Refer to AutoQuotes for list pricing.

UTILITY INFORMATION

| BTUs EACH BURNER | STD NON-CLOG | STAR/SAUTE' | WAVY NON-CLOG | PYROMAX | (A) CNV OVEN PER CAVITY | (D) STD OVEN PER CAVITY | GRIDDLE 12" | GRIDDLE 24" | GRIDDLE 36" | CHARBROILER 24" | CHARBROILER 36" | HOT TOP 12" |
|------------------|--------------|-------------|---------------|---------|-------------------------|-------------------------|-------------|-------------|-------------|-----------------|-----------------|-------------|
| NAT | 33K | 33K | 27K | 40K | 32K | 45K | 18K | 48K | 64K | 64K | 96K | 24K |
| LP | 24K | 24K | 24K | 31K | 30K | 40K | 18K | 48K | 64K | 64K | 96K | 24K |

- GAS:**
- One 3/4" female connection.
 - Required minimum inlet pressure
 - Natural gas 7" W.C.
 - Propane gas 11" W.C.
- ELECTRICAL:** (for Gas models with convection ovens)
- Standard -115/60/1 furnished with 6' cord with 3-prong plug. Total max amps 5.9 per convection oven base.
 - Optional -208/60/1, 50/60/1 phase. Supply must be wired to junction box with terminal block located at rear. Total max amps 2.7.
- ELECTRICAL:** (For Optional Hybrid Electric Ovens)
- H436_D - 208/60/1- 39 amps, 220/60/1-37 amps, 240/60/1-34 amps
 H436_A - 208/60/1-32 amps, 220/60/1-31 amps, 240/60/1-27 amps

MISCELLANEOUS

- If using Flex-Hose, the I.D. should not be smaller than 3/4" and must comply with ANSI Z 21.69.
 - If casters are used with flex hose, a restraining device should be used to eliminate undue strain on the flex hose.
 - For installation on combustible floors (with 6" high legs or casters) and adjacent to combustible walls, allow 10" clearance.
 - Clearance to noncombustible construction is 10" for charbroilers and 0" for all other tops and bases.
 - Recommended - Install under vented hood.
 - Check local codes for fire, installation and sanitary regulations.
 - If the unit is connected directly to the outside flue, an A.G.A approved down draft diverter must be installed at the flue outlet of the oven.
 - Two speed motors are not available on Restaurant Range Convection Ovens.
- NOTICE:** Southbend has a policy of continuous product research and improvement. We reserve the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions or replacements for previously purchased equipment.

OPTIONS AND ACCESSORIES

- 5" flue riser
- 10" Flue Riser
- 3/4" quick disconnect with flexible hose complies with ANSI Z 21.69 (specify 3ft, 4ft, 5ft)
- Casters-all swivel-front with locks
- Hot Top plate - plate replaces 2 Open burners
- Cabinet base doors (No Charge)
- Extra Oven Racks
- Various salamander & cheesemelter mounts available. (Please refer to the price list)
- Rear step up burners
- Flame Failure available (Contact factory for available model numbers)
- Battery spark ignition for open tops, charbroilers, griddles and hot tops

**INTENDED FOR COMMERCIAL USE ONLY.
 NOT FOR HOUSEHOLD USE.**

1100 Old Honeycutt Road, Fuquay-Varina, NC 27526
 (919) 762-1000 www.southbendnc.com

