

MODEL: _____ PROJECT: _____ ITEM #: _____ QTY: _____

PRODUCT IMAGE



18-W66R-7 SHOWN

AVAILABLE IN 1800 or 2100 SERIES

OPTIONAL ACCESSORIES

- **C-19** Stainless Steel Divider (Specify Model)
- **C-21** Bottle Wells (6 pack)
- **KR-501** Towel Ring
- **C-32** Condiment Tray
- **30-160** Perforated Dump Basket (Dump Sinks)
- **C-34** Stainless Steel Perforated Bottom (24", No Cold Plate)
- **C-35** Stainless Steel Perforated Bottom (30"+, No Cold Plate)
- **C-39** Right End Side Splash
- **C-40** Left End Side Splash
- **SC"XX"H** Partial Sliding Cover ("XX" denotes size of Ice Bin)
- **SC"XX"F** Full Sliding Cover ("XX" denotes size of Ice Bin)
- **C-43** Bottle Wells (2 pack)
- **C-46** Upgrade: 8 Circuit Cold Plate
- **C-70** Upgrade: Stainless Steel Legs
- **H-109** Upgrade: Royal Series Low Lead Faucet
- **S-"XX"** Single Speedrail ("XX" denotes size of 24", 30", or 36")
- **D-"XX"** Double Speedrail ("XX" denotes size of 24", 30", or 36")

STANDARD FEATURES

- **Drainboard**
20 gauge stainless steel
- **Dump Sink**
20 gauge stainless steel. 10" x 14" x 6" deep bowl with 1 1/2" drain in center
- **Blender Shelf**
22 gauge stainless steel
- **Interior (Ice Bin)**
20 gauge stainless steel
- **Cold Plate**
Cast aluminum post mix plate with 7 circuits. Plate is sealed into bottom. Each circuit is 5/16" OD stainless steel tubing. Two full with remainder to be half circuits. Bump and swedge fittings on ends
- **Front Apron**
22 gauge stainless steel clad over 20 gauge galvanized steel
- **Backsplash**
22 gauge stainless steel
- **Back and Bottom**
20 gauge galvanized steel
- **Legs**
1 5/8" tubular 16 gauge galvanized steel with grey plastic bullet foot
- **Electrical (Blender)**
Duplex outlet located underneath Blender Shelf
- **Plumbing**
Hot/Cold Water: 1/2" IPS
Cold Plate: 1/2" IPS drain connection
Drainboard, No Cold Plate: 1" IPS drain connection
Dump Sink: 1 1/2" IPS drain connection
- **Low Lead Compliance**
Low Lead Compliant faucet options are available to meet California AB-1953 and Vermont S152 standards



CERTIFICATIONS:

APPROVED BY:

Due to our commitment to continued product improvement, specifications are subject to change without notice.

Printed in the USA

Krowne Metal Corporation

100 Haul Rd. Wayne, NJ 07470 • Toll Free: (800) 631-0442 • Fax: (973) 872-1129
sales@krowne.com • www.krowne.com • www.facebook.com/KrowneMetal • www.twitter.com/KrowneMetal

Rev. 08/2015
No. 4.1



STANDARD SERIES UNDERBAR WORKSTATIONS

MODEL: _____ PROJECT: _____ ITEM #: _____ QTY: _____

1800 SERIES

	Model Numbers	Overall Length	Ice Bin Length/Depth	Drainboard Length	Blender/Dump Length	Ice Bin Location	Blender Location	Cold Plate Circuits	Weight (lbs.)
		A	B	C	D				
	18-W42L	3'-6"	24"/12"	N/A	18"	Left	Right	N/A	100
	18-W42R	3'-6"	24"/12"	N/A	18"	Right	Left	N/A	100
	18-W48L	4'-0"	30"/12"	N/A	18"	Left	Right	N/A	110
	18-W48R	4'-0"	30"/12"	N/A	18"	Right	Left	N/A	110
	18-W54L	4'-6"	36"/12"	N/A	18"	Left	Right	N/A	115
	18-W54R	4'-6"	36"/12"	N/A	18"	Right	Left	N/A	115
	18-W42L-7	3'-6"	24"/12"	N/A	18"	Left	Right	7	150
	18-W42R-7	3'-6"	24"/12"	N/A	18"	Right	Left	7	150
	18-W48L-7	4'-0"	30"/12"	N/A	18"	Left	Right	7	160
	18-W48R-7	4'-0"	30"/12"	N/A	18"	Right	Left	7	160
	18-W54L-7	4'-6"	36"/12"	N/A	18"	Left	Right	7	170
	18-W54R-7	4'-6"	36"/12"	N/A	18"	Right	Left	7	170
	18-W66L	5'-6"	24"/12"	24"	18"	Center	Left	N/A	150
	18-W66R	5'-6"	24"/12"	24"	18"	Center	Right	N/A	150
	18-W66L-7	5'-6"	24"/12"	24"	18"	Center	Left	7	230
	18-W66R-7	5'-6"	24"/12"	24"	18"	Center	Right	7	230
	18-D48L	4'-0"	24"/12"	24"	N/A	Left	N/A	N/A	75
	18-D48R	4'-0"	24"/12"	24"	N/A	Right	N/A	N/A	75
	18-D48L-7	4'-0"	24"/12"	24"	N/A	Left	N/A	7	100
	18-D48R-7	4'-0"	24"/12"	24"	N/A	Right	N/A	7	100

2100 SERIES

	Model Numbers	Overall Length	Ice Bin Length/Depth	Drainboard Length	Blender/Dump Length	Ice Bin Location	Blender Location	Cold Plate Circuits	Weight (lbs.)
		A	B	C	D				
	21-W42L	3'-6"	24"/12"	N/A	18"	Left	Right	N/A	105
	21-W42R	3'-6"	24"/12"	N/A	18"	Right	Left	N/A	105
	21-W48L	4'-0"	30"/12"	N/A	18"	Left	Right	N/A	115
	21-W48R	4'-0"	30"/12"	N/A	18"	Right	Left	N/A	115
	21-W54L	4'-6"	36"/12"	N/A	18"	Left	Right	N/A	120
	21-W54R	4'-6"	36"/12"	N/A	18"	Right	Left	N/A	120
	21-W42L-7	3'-6"	24"/12"	N/A	18"	Left	Right	7	170
	21-W42R-7	3'-6"	24"/12"	N/A	18"	Right	Left	7	170
	21-W48L-7	4'-0"	30"/12"	N/A	18"	Left	Right	7	180
	21-W48R-7	4'-0"	30"/12"	N/A	18"	Right	Left	7	180
	21-W54L-7	4'-6"	36"/12"	N/A	18"	Left	Right	7	195
	21-W54R-7	4'-6"	36"/12"	N/A	18"	Right	Left	7	195
	21-W66L	5'-6"	24"/12"	24"	18"	Center	Left	N/A	170
	21-W66R	5'-6"	24"/12"	24"	18"	Center	Right	N/A	170
	21-W66L-7	5'-6"	24"/12"	24"	18"	Center	Left	7	230
	21-W66R-7	5'-6"	24"/12"	24"	18"	Center	Right	7	230
	21-D48L	4'-0"	24"/12"	24"	N/A	Left	N/A	N/A	80
	21-D48R	4'-0"	24"/12"	24"	N/A	Right	N/A	N/A	80
	21-D48L-7	4'-0"	24"/12"	24"	N/A	Left	N/A	7	110
	21-D48R-7	4'-0"	24"/12"	24"	N/A	Right	N/A	7	110



APPROVED BY:

Due to our commitment to continued product improvement, specifications are subject to change without notice.

Printed in the USA

Krowne Metal Corporation

100 Haul Rd. Wayne, NJ 07470 • Toll Free: (800) 631-0442 • Fax: (973) 872-1129

sales@krowne.com • www.krowne.com • www.facebook.com/KrowneMetal • www.twitter.com/KrowneMetal

Rev. 08/2015
No. 4.1