



iT0450 Ice Cube Machine

Models

IDT0450A IYT0450A

IDT0450W IYT0450W





Ice Machine Electric

115/60/1 standard (208-230/60/1also available)

Minimum circuit ampacity:

115v: 11.9, 208-230v: 5.6 Air-cooled: Water-cooled: 115v: 11.2, 208-230v: 5.3

Maximum fuse size:

Air Cooled: 20 amps

Water cooled & 208-230 V: 15 amps

Specifications

BTU Per Hour:

3,800 (average), and 6,000 (peak)

Refrigerant:

R410A CFS - Free Lowers global warming by 48%

Operating Limits:

- Ambient Temperature Range: 40° to 110°F (4.4° to 43.3°C) Water Temperature Range: 40° to 90°F (4.4° to 32.2°C)
- Water Pressure Ice Maker Water In: Min. 20 psi (137.9 kPA) Max. 80 psi (551.1 kPA)

Designed for operators who know that ice is critical to their business, the Indigo NXT Series ice machine's preventative diagnostics continually monitor itself for reliable ice production. Improvements in cleanability and programmability make your ice machine easy to own and less expensive to operate.

- New levels of Performance Showcasing an average of 9% lower energy consumption, up to 12% increase in ice production and a 19% reduction in condenser water usage and a 5% reduction in potable water usage. . This translates into lower cost of ownership over the life of your machine.
- easyTouch® Display New icon based touch screen takes the guess work out of owning and operating an ice machine.
- Programmable Ice Production Now its super easy to program your ice machine to be off at certain times of the day to save money with fluctuating electrical rates. Also programmable by daily ice production volume.
- Easy to Clean Foodzone Hinge front door swing out for easy access. Removable water-trough, distribution tube, curtain, water probe and water pump for fast and efficient cleaning. Selected components are made with AlphaSan® antimicrobial.
- Intelligent Diagnostics Provides 24 hour preventative maintenance and diagnostic feedback for trouble free
- Acoustical Ice Sensing Probe Unique patented technology allows for reliable operation in challenging water conditions and environments
- DuraTech® Exterior Provides superior corrosion resistant above stainless steel. Innovative clear-coat resists fingerprints and dirt making it easier to keep clean.
- Available LuminIce® II Growth Inhibitor Controls the growth of bacteria and yeast within the Food zone keeping the machine cleaner longer. A new indicator in the display keeps you abreast of the operational status.



Ice Shape



Half Dice 3%" x 11%" x 7%" (.95 x 2.86 x 2.22 cm)



Dice %" x %" x %" (2.22 x 2.22 x 2.22 cm)














COMPANY WITH QUALITY SYSTEM



Tel: 1.920.682.0161 Fax: 1.920.683.7589





MANITOWOC*



iT0450 on D-400 Storage Bin

- (2) Options
- (B) 3/8" (0.95 cm) F.P.T. Water Condenser Inlet (water-cooled units)
- © 1/2" (1.27 cm) F.P.T. Water Condenser Outlet (water-cooled units)
- 1/2" (1.27 cm) Auxillary Base Drain Socket
- © 3/8" (0.95 cm) F.P.T. Ice Making Water Inlet
- (F) 1/2" (1.27 cm) F.P.T. Ice Making Water Drain



Installation Note Minimum installation clearance:

Top/side: 12" (30.50 cm)Back is 5" (12.7

1.75" (4.45 cm) 4.00" (10.16 cm) 5.25" (13.34 cm) 34.00" (86.36 cm)

Space-Saving Design





	iT0450 D-400	iT0450 D-570
Height	59.50" 151.13 cm	71.50" 181.61 cm
Width	30.00" 76.2 cm	30.00" 76.2 cm
Depth	34.00" 86.30 cm	34.00" 86.30 cm
Bin Storage	365 lbs. 165.7 kgs.	543 lbs. 241.1 kgs.

Height includes adjustable bin legs 6.00" to 8.00", (15.24 to 20.32 cm) set at 6.00" (15.24 cm). Bin capacity is based on 90% of the volume x 33 lbs/ft3 average density of ice.

Specifications

		lce	lce Producti	on 24 Hours	Power Usage kWh/100 lbs. @90°Air/70°F	Potable Water Usage/100 lbs.			
	Model Shape		70°Air/ 50°F Water	90°Air/ 70°F Water	1 Ph	45.4 kgs. of Ice			
	IDT04F0A	0A dice	470 lbs.	358 lbs.		19 Gal.			
AIR COOLED	IDT0450A		213 kgs	162 kgs	5.63 ★	71.9 L			
₹ 8	IYT0450A	half-dice	490 lbs.	378 lbs.	-	19 Gal.			
		10	222 kgs	171 kgs	5.52 ★	71.9 L			
	IDT0450W	dice	430 lbs.	360 lbs.	4.75	19 Gal.			
a	ID10450W		195 kgs	163 kgs	4.75	71.9 L			
COOLED	IYT0450W	half-dice	470 lbs.	420 lbs.	4.70	19 Gal.			
	111045000		213 kgs.	191 kgs	4.70	71.9 L			
ATER	* Water souled Condenser Water Heage / 100 lbs /45 4 kgs Of Iso 140 gal/ 520 L								

24.00" (60.96 cm)

21.50" (54.61 cm)

32.00" (81.28 cm)

2.47" (6.27 cm)

115/60/1

* Water-cooled Condenser Water Usage / 100 lbs. /45.4 kgs. Of Ice: 140 gal/ 530 L. *Water-cooled models are excluded from ENERGY STAR qualification.

Order separately: Ice storage bin for all units ★ENERGY STAR® 3.0

Accessories

LuminIce® II Growth Inhibitor

reduces yeast and bacteria growth for a cleaner ice machine.



External Scoop holder

Protect the ice scoop with the NSF approved versatile scoop holder.



Arctic Pure® Water Filters

Reduces sediment and chlorine odors for better tasting ice.



iAuCS®

schedules and performs routine ice machine cleaning automatically.



Welbilt reserves the right to make changes to the design or specifications without prior notice.

2110 South 26th Street Manitowoc, WI 54220 Tel: 1.920.682.0161 Fax: 1.920.683.7589 www.manitowocice.com 6478 01/18







Ice Storage Bins

Model D320 D400 D570 D970

D Bins

.75" (1.90 cm) Bin drain



D320 210 lbs. (95 kgs) (Available January)



D400 290 lbs. (132 kgs) (Available January)



D420 310 lbs. (141 kgs) (Available January)



Ergonomic NSF approved sanitary ice scoop included



D570 430 lbs. (195 kgs) (Available January)



D970 710 lbs. (323 kgs)

D Bin Features

New Sanitary Scoop Ergonomic NSF approved sanitary ice scoop included with each bin. Built-in knuckle and thumb guard. Unique molded retaining lip allows maximum scooping every time. Per scoop capacity approximately 5.3/ lbs (2.4 kg)

Scoop Holder options New built-in scoop holder, keeps the ice scoop handle above the ice, or purchases the optional NSF approved External Scoop Holder Kit # K00461. (Available January 2018)

New Door design Clever built in side grips allow you to lift the bin door from anywhere you are standing (left, right or center) even when you have just one hand free.

Foamed Insulated Door

Insulates the ice bin, reduces sweat on the door, helps keep ice lasting longer.

Stay up door Unique cammed bin door self-latch keeps the door in the open position and keeps the employee safe when scooping ice.

Ergonomic Door design Door is angled 53 degrees to allow for easier access to the ice in the bin especially when scooping from the bottom.

Duratech Metal Finish Manitowoc exterior material has better corrosion resistance than stainless steel, is smudge resistant and easy to keep clean.

New Bin liner Polyurethane Artic Blue bin liner accentuates the crisp clear ice from a Manitowoc Ice Machine.

Warranty

Bin & Accessories: 3 Year Parts & Labor.

	D-Bin Capacities							D-Bin Dimensions					
	*Application Capacity		**2017 AHRI Capacity		**2018 AHRI Capacity		Height		Width		Depth		
D Bin Model	lbs.	kgs	lbs.	kgs.	Cu. ft	Cu. M	in.	cm	in.	cm	in.	cm	
D320	264	119.90	210	95.25	8.9	0.25	38	96.5	22	55.9	34	86.4	
D420	383	173.79	310	140.61	12.9	0.37	50	127	22	55.9	34	86.4	
D400	365	165.70	290	131.54	12.3	0.35	38	96.5	30	76.2	34	86.4	
D570	532	241.14	430	195.05	17.9	0.51	50	127	30	76.2	34	86.4	
D970	882	400.11	710	322.05	29.7	0.84	50	127	48	121.9	34	86.4	

*Application Capacity is based on 90% of the volume x 33 lbs/ft3 average density of ice. lce must be managed

**2017 Approved AHRI capacity is based on 80% of the total volume x 30 lbs/ft3 average density of ice

***2018 AHRI certified measurement for bin capacity

Above bin heights include leg height of of 6" / 15.24 cm

All bins include sanitary plastic ice scoop and one set of adjustable (6 in to 7.75 in / 15.24 to 20.32 cm) chrome legs

External Scoop holder order separately Kit # 000461







Welbilt reserves the right to make changes to the design or specifications without prior notice.