



## iT1200 Ice Cube Machine

#### Models IDT1200A IYT1200A IDT1200W IYT1200W IDT1200N IYT1200N



### Ice Machine Electric

208-230/60/1 standard (208-230/60/3 also available)

#### Minimum circuit ampacity:

8.6 3ph Air-cooled: 14.2 *1ph* Water-cooled: 13.4 1ph 7.9 3ph 10.1 *3ph* 10.9 Remote: 1ph Maximum fuse size:

15 *3ph* 20 1ph Air-cooled: Water-cooled: 20 1ph 15 3ph 15 3ph Remote: 15 1ph

## Specifications

#### **BTU Per Hour:**

16,200 (average), and 19,100 (peak)

#### Refrigerant:

R410A CFS - Free Lowers global warming by 48%

#### **Operating Limits:**

- Ambient Temperature Range: 40° to 110°F (4.4° to 43.3°C) Water Temperature Range: 40° to 90°F (4.4° to 32.2°C)
- Water Pressure Ice Maker Water In: Min. 20 psi (137.9 kPA) Max. 80 psi (551.1 kPA)

Designed for operators who know that ice is critical to their business, the Indigo NXT Series ice machine's preventative diagnostics continually monitor itself for reliable ice production. Improvements in cleanability and programmability make your ice machine easy to own and less expensive to operate.

- New levels of Performance Showcasing an average of 5% lower energy consumption and a 22% reduction in condenser water usage. This translates into lower cost of ownership over the life of your machine.
- easyTouch® Display New icon based touch screen takes the guess work out of owning and operating an ice machine.
- Programmable Ice Production Now its super easy to program your ice machine to be off at certain times of the day to save money with fluctuating electrical rates. Also programmable by daily ice production volume.
- Easy to Clean Foodzone Hinge front door swing out for easy access. Removable water-trough, distribution tube, curtain, water probe and water pump for fast and efficient cleaning. Selected components are made with AlphaSan® antimicrobial.
- Intelligent Diagnostics Provides 24 hour preventative maintenance and diagnostic feedback for trouble free
- Acoustical Ice Sensing Probe Unique patented technology allows for reliable operation in challenging water conditions and environments
- **DuraTech® Exterior** Provides superior corrosion resistant above stainless steel. Innovative clear-coat resists fingerprints and dirt making it easier to keep clean.
- Available LuminIce® II Growth Inhibitor Controls the growth of bacteria and yeast within the Food zone keeping the machine cleaner longer. A new indicator in the display keeps you abreast of the operational status.



## Ice Shape



**Half Dice** 3%" x 11%" x 7%" (.95 x 2.86 x 2.22 cm)



Dice %" x %" x %" (2.22 x 2.22 x 2.22 cm)













COMPANY WITH **QUALITY SYSTEM** 








## iT1200 on D-570 Storage Bin

- (B) 3/8" (0.95 cm) F.P.T. Water Condenser Inlet (water-cooled units)
- (water-cooled units)

  (C) 1/2" (1.27 cm) F.P.T. Water Condenser Outlet (water-cooled units)
- ① 1/2" (1.27 cm) Auxillary Base Drain Socket ⑥ 3/8" (0.95 cm) F.P.T. Ice Making Water Inlet
- (E) 3/8" (0.95 cm) F.P.T. Ice Making Water Inlet (F) 1/2" (1.27 cm) F.P.T. Ice Making Water Drain
- (G) 3/4" (1.91 cm) Bin Drain

## Installation Note



## Space-Saving Design





	iT1200 D-570	iT1200 D-970
Height	79.50" 201.93 cm	79.50" 201.93 cm
Width	30.00" 76.20 cm	48.00" 121.92 cm
Depth	34.00" 86.30 cm	34.00" 86.30 cm
Bin Storage	543 lbs. 241.1 kgs.	882 lbs. 400.1 kgs.

Height includes adjustable bin legs 6.00" to 8.00", (15.24 to 20.32 cm) set at 6.00" (15.24 cm). Bin capacity is based on 90% of the volume x 33 lbs/ft3 average density of ice.

\* K00458 bin adapter required

## Specifications

		lce	Ice Producti	on 24 Hours	kWh/1	Usage 00 lbs. ir/70°F	Potable Water Usage/100 lbs.	
	Model	Shape	70°Air/ 50°F Water	90°Air/ 70°F Water	1 Ph	3 Ph	45.4 kgs. of Ice	
	IDT1200A	dice	1196 lbs.	950 lbs.	4.80	4.80	19.9 Gal.	
~띰	ID11200A		542 kgs	431 kgs	4.00	4.00	75.3 L	
AIR COOLED	IYT1200A	half-dice	1213 lbs.	950 lbs.	4.75	4.75	19.9 Gal.	
	1111200A		550 kgs	431 kgs	4./5	4.75	75.3 L	
	IDT1200W	dice	1078 lbs.	900 lbs.	4.16	4.16	19.9 Gal.	
<b>⊞</b>	101120000		489 kgs	408 kgs	4.16	4.16	75.3 L	
COOLED	IYT1200W	half-dice	1138 lbs.	965 lbs.	4.00		19.9 Gal.	
	111120000		516 kgs.	438 kgs	4.00	4.00	75.3 L	
떒								

\* Water-cooled Condenser Water Usage / 100 lbs. /45.4 kgs. Of Ice: 140 gal/ 530 L. \*Water-cooled models are excluded from ENERGY STAR qualification.

REMOTE	IDT1200N	dice	1127 lbs.	955 lbs.	4.63	4.63	19.9 Gal.		
			511 kgs	435 kgs	4.03	4.03	75.3 L		
	IYT1200N	half-dice	1215 lbs.	1030 lbs.	4.43	4.43	19.9 Gal.		
	IYIIZUUN		551 kgs	454 kgs	4.43	4.43	75.3 L		

Order Separately ice storage bin for all units, JCT1200-A vertical condenser order separately for Remote cooled units

### Accessories

#### LuminIce® II Growth Inhibitor reduces yeast and bacteria growth for a cleaner ice machine.



#### External Scoop holder

Protect the ice scoop with the NSF approved versatile scoop holder.



#### Arctic Pure® Water Filters

Reduces sediment and chlorine odors for better tasting ice.



#### iAuCS®

schedules and performs routine ice machine cleaning automatically.



Welbilt reserves the right to make changes to the design or specifications without prior notice.

2110 South 26th Street Manitowoc, WI 54220 Tel: 1.920.682.0161 Fax: 1.920.683.7589 www.manitowocice.com 6561B 06/19







## Ice Storage Bins

# Model D320 D400 D420 D570 D970

### **D** Bins

.75" (1.90 cm) Bin drain



D320 210 lbs. (95 kgs)



D400 290 lbs. (132 kgs)



D420 310 lbs. (141 kgs)



Ergonomic NSF approved sanitary ice scoop included



D570 430 lbs. (195 kgs)



D970 710 lbs. (323 kgs)

#### D Bin Features

New Sanitary Scoop Ergonomic NSF approved sanitary ice scoop included with each bin. Built-in knuckle and thumb guard. Unique molded retaining lip allows maximum scooping every time. Per scoop capacity approximately 5.3/ lbs (2.4 kg)

Scoop Holder options New built-in scoop holder, keeps the ice scoop handle above the ice, or purchases the optional NSF approved External Scoop Holder Kit # K00461. (Available January 2018)

**New Door design** Clever built in side grips allow you to lift the bin door from anywhere you are standing (left, right or center) even when you have just one hand free.

#### **Foamed Insulated Door**

Insulates the ice bin, reduces sweat on the door, helps keep ice lasting longer.

**Stay up door** Unique cammed bin door self-latch keeps the door in the open position and keeps the employee safe when scooping ice.

**Ergonomic Door design** Door is angled 53 degrees to allow for easier access to the ice in the bin especially when scooping from the bottom.

**Duratech Metal Finish** Manitowoc exterior material has better corrosion resistance than stainless steel, is smudge resistant and easy to keep clean.

**New Bin liner** Polyurethane Artic Blue bin liner accentuates the crisp clear ice from a Manitowoc Ice Machine.

## Warranty

Bin & Accessories: 3 Year Parts & Labor.

			D-Bin C	apacities	D-Bin Dimensions							
	1	ication acity		7 AHRI acity	**2018 AHRI Capacity		Height		Width		Depth	
D Bin Model	lbs.	kgs	lbs.	kgs.	Cu. ft	Cu. M	in.	cm	in.	cm	in.	cm
D320	264	119.90	210	95.25	8.9	0.25	38	96.5	22	55.9	34	86.4
D420	383	173.79	310	140.61	12.9	0.37	50	127	22	55.9	34	86.4
D400	365	165.70	290	131.54	12.3	0.35	38	96.5	30	76.2	34	86.4
D570	532	241.14	430	195.05	17.9	0.51	50	127	30	76.2	34	86.4
D970	882	400.11	710	322.05	29.7	0.84	50	127	48	121.9	34	86.4

\*Application Capacity is based on 90% of the volume x 33 lbs/ft3 average density of ice. Ice must be managed

\*\*2017 Approved AHRI capacity is based on 80% of the total volume x 30 lbs/ft3 average density

\*\*\*2018 AHRI certified measurement for bin capacity

Above bin heights include leg height of of 6" / 15.24 cm
All bins include sanitary plastic ice scoop and one set of adjustable (6 in

to 7.75 in / 15.24 to 20.32 cm) chrome legs

External Scoop holder order separately Kit # 000461







Welbilt reserves the right to make changes to the design or specifications without prior notice.







#### **D** Bins

יווט כ	9												
				Indi	go Ice Ma	achines S	erie	S					
		Machine	iT420	iT620	i300	iT450	iT	500	iF600	.,	'		iT1500, iT1900
M	achine Cap @90/70 F		375	465	240	378	4	140	555, 5	30 710, 71	4 950, 100	1200 0 1470 1600	1360, 1455
Bins	Bin Cap	Width	22"	22"	30"	30"	3	30"	30'	' 30"	30"	30"	48"
D320	264	22"	*	*									
D420	383	22"	*	*									
D400	365	30"	K00472	K00472	*	*		*	*	NR	NR	NR	
D570	532	30"	K00472	K00472	*	*		*	*	*	*	NR	
D970	882	48"	NR	NR	NR	K00470	KO	0470	K004	70 K0047	0 K00470	K00471 + K00470	*
				Manitow	oc Flaker	and Nug	get	Machir	nes				
Machin		ne RNS0308 & RNF320	RFS0300 &RFF320	RNF620	RFF06	520	RNF10	020	RFF1220	RNF1100	RFF1300	RFF2200C	
Mac	hine cap		251	286	451	540	)	825	5	958	825	874	1702
Bins	Bin ca	) Widt	h 22"	22"	22"	22	"	22'	"	22"	30"	30"	36.7"
D320	264	22"	*	*	NR	NF	?	NR	2	NR			
D420	383	22"	*	*	*	*		NR	R	NR			
D400	365	30"	K00472	K00472	K00472	2 K004	72	NR	2	NR	NR	NR	
D570	532	30"	NR	K00472	K00472	2 K004	72	NR	R	NR	*	*	
D970	882	48"	NR	NR	K00473	3 K004	73	K0047 2 use		K00473 if 2 used.	K00470	K00470	K00470

An optional adapter is required when putting a narrower ice machine on a wider bin. \* No adapter is needed

## Available Accessories See price book for replacement: scoops, legs, specialty legs and casters

#### **K00146 Convenient** Ice Bagger

Includes bagger, D-bin adapter, and 250 bags and ties (Not for D320 or D400) Order K00068 replacement bags



#### **K00461 External Scoop Holder**

NSF approved. Can be mounted on the left or right side of bins, horizontally or vertically or on a wall.









#### **K00463 Metal Scoop**

Indestructible NFS approved aluminum alloy with sanitary knuckle and thumb guard. Works with K00461external scoop holder or hangs inside the D-Bin series. Limited life time guarantee. (Available October 2018)

#### K00462 **Secure Fastening Kit**

Securely fast the Indigo ice machine head to the pre-drilled inserts on the back of the D-bin series. Stainless steel flanged feet attach to bin and can be screwed to the floor





Welbilt reserves the right to make changes to the design or specifications without prior notice.

2110 South 26th Street Manitowoc, WI 54220

Tel: 1.920.682.0161 Fax: 1.920.683.7589

www.manitowocice.com 6453B 09/18



NR= Not Recommend. Bin too small or too large for application.

Putting a wider machine on narrower bin is not an option. Machines side by side must be water cooled or remote.

Application Bin Capacity shown in lbs using the AHRI rating based on 90% of total volume x 33 lbs/ft3 average density of ice.

Machine capacity shown in lbs/24hrs using the AHRI rating base at 90F ambient, 70F water temperature