



iF-300 Ice Cube Machine

Models ☐ IYF-0300A IDF-0300A IDF-0300W IYF-0300W



Ice Machine Electric

115/60/1 standard. (208-230/60/1 and 230/50/1 also available.)

Minimum circuit ampacity:

Air-cooled: 10.8 Water-cooled: 10 Maximum fuse size:

Specifications

BTU Per Hour:

15 amps 1ph

4,600 (average), 5,450 (peak)

Refrigerant:

R-404A CFC-free

Operating Limits:

- · Ambient Temperature Range: 40 to 110 F (4.4 to 43.3 C) Water Temperature Range: 40 to 90 F (4.4 to 32.2 C)
- · Water Pressure Ice Maker Water In:

Min. 20 psi (137.9 kPA) Max. 80 psi (551.1 kPA)

Designed for operators who know that ice is critical to their business, the Indigo®NXT Series ice machine's preventative diagnostics continually monitor itself for reliable ice production. Improvements in cleanability and programmability make your ice machine easy to own and less expensive to operate.

- Space-Saving Design Measures only 16.5" high (42 cm) and 30" wide (76.20 cm) allowing it to fit on top of dispensers when a low ceiling is an issue.
- easyTouch® Display- New icon based touch screen takes the guess work out of owning and operating an ice machine.
- Programmable Ice Production Now its super easy to program your ice machine to be off at certain times of the day to save money with fluctuating electrical rates. Also programmable by daily ice production volume.
- Easy to Clean Foodzone Hinged front door swings out for easy access. Removable water-trough, distribution tube, curtain, and sensing probes for fast and efficient cleaning. Select components made with AlphaSan® antimicrobial.
- Intelligent Diagnostics provide 24 hour preventative maintenance and diagnostic feedback for trouble free
- · Acoustical Ice Sensing Probe Unique patented technology allows for reliable operation in challenging water conditions and environments.
- **DuraTech™ Exterior** provides superior corrosion resistant above stainless steel. Innovative clear-coat resists fingerprints and dirt making it easier to keep clean.
- Avaiable LuminIce II Growth Inhibitor- Controls the growth of bacteria and yeast with the food zone keep the machine cleaner longer. A new indicator in the display keeps you abreast of the operational status.



Ice Shape





Dice %" x %" x %" (2.22 x 2.22 x 2.22 cm)














COMPANY WITH QUALITY SYSTEM CERTIFIED BY DNV = ISO 9001:2008 =



Tel: 1.920.682.0161 Fax: 1.920.683.7589









iF0300 on a D400 24.50" (62.23 cm) Storage Bin Installation Note Water Cooled clearance: Top/Sides: 8" (20.3 cm) 16.50" (41.91 cm) Back: 5" (12.7 cm) Air Cooled clearance: Top/Sides: 16" (40.6 cm) Back: 5" (12.7 cm) 32.00" (81.30 cm) 5.25" (13.34 cm) **G** 30.00" (76.20 cm) 34.00" (86.36 cm) 19.00" (48.26 cm)

Space-Saving Designs



iF0300 D-400

Height 54.50" 138.43 cm

Width

30.00"

76.20 cm Depth 34.00"

86.30 cm

Bin 365 lbs. Storage 165.7 kgs.

Height includes adjustable bin legs 6.00" to 8.00", (15.24 to 20.32 cm) set at 6.00" (15.24 cm).

Storage bin rated at application capacity based on 90% of the volume x 33 lbs/ft3 average density of ice.

- (2) Options
- (B) 3/8" (0.95 cm) F.P.T. Water Condenser Inlet (water-cooled units)
- © 1/2" (1.27 cm) F.P.T. Water Condenser Outlet (water-cooled units)
- 1/2" (1.27 cm) Auxillary Base Drain Socket
- (E) 3/8" (0.95 cm) F.P.T. Ice Making Water Inlet
- (F) 1/2" (1.27 cm) F.P.T. Ice Making Water Drain (G) 3/4" (1.91 cm) Bin Drain

Specifications

		L	Ice Producti	on 24 Hours	Power Usage kWh/100 lbs. @90°Air/70°F	Water Usage/ 100 lbs. 45.4 kgs. of Ice					
	Model	Ice Shape	70°Air/ 50°F Water	90°Air/ 70°F Water							
Α.	IDF0300A	dice	325 lbs.	240 lbs.	6.95	20.0 gal					
AIR-COOLED	IDF0300A		147 kgs.	108 kgs.	6.95	75.7 L					
	IYF0300A	half-dice	325 lbs.	240 lbs.	6.95	20.0 gal					
	1110300A		147 kgs.	108 kgs.	0.93	75.7 L					
	IDF0300W	dice	310 lbs.	250 lbs.	5.45	20.0 gal					
ED	IDF0300W		140 kgs.	118 kgs.	5.45	75.7 L					
Ş	IYF0300W	half-dice	310 lbs.	260 lbs.	5.50	20.0 gal					
WATER-COOLED	111030000		140 kgs.	118 kgs.	5.50	75.7 L					
W	* Water-cooled Condenser Water Usage / 100 lbs. /45.4 kgs. Of Ice: 180 gal / 681 L .										

Order ice storage bin separately.

Accessories

LuminIce® II Growth Inhibitor reduces yeast and

reduces yeast and bacteria growth for a cleaner ice machine.



External Scoop holder Protect the ice sco

Protect the ice scoop with the NSF approved versatile scoop holder.



* Water-cooled models are excluded from ENERGY STAR qualification.

Arctic Pure® Water Filters Reduces sediment

and chlorine odors for better tasting ice.



iAuCS®

schedules and performs routine ice machine cleaning automatically.



Welbilt reserves the right to make changes to the design or specifications without prior notice.

2110 South 26th Street Manitowoc, WI 54220 Tel: 1.920.682.0161 Fax: 1.920.683.7589 www.manitowocice.com 6585A 07/19







Ice Storage Bins


Model

D400


☐ D420 ☐ D570 ☐ D970

D Bins

.75" (1.90 cm) Bin drain



D320 210 lbs. (95 kgs)



D400 290 lbs. (132 kgs)



D420 310 lbs. (141 kgs)



Ergonomic NSF approved sanitary ice scoop included



430 lbs. (195 kgs)



710 lbs. (323 kgs)

D Bin Features

New Sanitary Scoop Ergonomic NSF approved sanitary ice scoop included with each bin. Built-in knuckle and thumb guard. Unique molded retaining lip allows maximum scooping every time. Per scoop capacity approximately 5.3/ lbs (2.4 kg)

Scoop Holder options New built-in scoop holder, keeps the ice scoop handle above the ice, or purchases the optional NSF approved External Scoop Holder Kit # K00461. (Available January 2018)

New Door design Clever built in side grips allow you to lift the bin door from anywhere you are standing (left, right or center) even when you have just one hand free.

Foamed Insulated Door

Insulates the ice bin, reduces sweat on the door, helps keep ice lasting longer.

Stay up door Unique cammed bin door self-latch keeps the door in the open position and keeps the employee safe when scooping ice.

Ergonomic Door design Door is angled 53 degrees to allow for easier access to the ice in the bin especially when scooping from the bottom.

Duratech Metal Finish Manitowoc exterior material has better corrosion resistance than stainless steel, is smudge resistant and easy to keep clean.

New Bin liner Polyurethane Artic Blue bin liner accentuates the crisp clear ice from a Manitowoc Ice Machine.

Warranty

Bin & Accessories: 3 Year Parts & Labor.

	D-Bin Capacities							D-Bin Dimensions						
	*Application Capacity		**2017 AHRI Capacity		**2018 AHRI Capacity		Height		Width		Depth			
D Bin Model	lbs.	kgs	lbs.	kgs.	Cu. ft	Cu. M	in.	cm	in.	cm	in.	cm		
D320	264	119.90	210	95.25	8.9	0.25	38	96.5	22	55.9	34	86.4		
D420	383	173.79	310	140.61	12.9	0.37	50	127	22	55.9	34	86.4		
D400	365	165.70	290	131.54	12.3	0.35	38	96.5	30	76.2	34	86.4		
D570	532	241.14	430	195.05	17.9	0.51	50	127	30	76.2	34	86.4		
D970	882	400.11	710	322.05	29.7	0.84	50	127	48	121.9	34	86.4		

*Application Capacity is based on 90% of the volume x 33 lbs/ft3 average density of ice.

**2017 Approved AHRI capacity is based on 80% of the total volume x 30 lbs/ft3 average density

***2018 AHRI certified measurement for bin capacity

Above bin heights include leg height of of 6" / 15.24 cm All bins include sanitary plastic ice scoop and one set of adjustable (6 in

to 7.75 in / 15.24 to 20.32 cm) chrome legs

External Scoop holder order separately Kit # 000461







Welbilt reserves the right to make changes to the design or specifications without prior notice.







D Bins

יווט כ	<i></i>													
				Indi	go Ice Ma	achines	Serie	25						
Machine		iT420	iT620	i300	iT450	i	T500 iF600, iF600C		,	900, 900C	iT1200, iT1200C	iF1400C iF1800C iF2100C	iT1500, iT1900	
Machine Capacity @90/70 F		375	465	240	378		440	555,	530 71	0, 714	950, 1000	1200 1470 1600	1360, 1455	
Bins Bin Cap \		Width	22"	22"	30"	30"		30"	30)"	30"	30"	30"	48"
D320	264	22"	*	*										
D420	383	22"	*	*										
D400	365	30"	K00472	K00472	*	*		* *			NR	NR	NR	
D570	532	30"	K00472	K00472	*	*		*	*		*	*	NR	
D970	882	48"	NR	NR	NR	K0047	КС	00470	K004	470 K0	00470	K00470	K00471 + K00470	*
				Manitow	oc Flaker	and Nu	gget	Machi	ines					
	Mac		RNS0308 & RNF320	RFS0300 &RFF320	RNF620) RFF	0620	RNF1	020	RFF12	20 F	RNF1100	RFF1300	RFF2200C
Machine cap			251	286	451	54	540		825			825	874	1702
Bins	Bin ca) Width	1 22"	22"	22"	2.	2"	22	2"	22"		30"	30"	36.7"
D320	264	22"	*	*	NR	N	NR		NR		NR			
D420	383	22"	*	*	*		*		NR		NR			
D400	365	30"	K00472	K00472	K00472	2 K00	K00472		NR		T	NR	NR	
D570	532	30"	NR	K00472	K00472	2 K00	472	N	R	NR		*	*	
D970	882	48"	NR	NR	K00473	3 K00	473	K004 2 us		K0047 2 use		(00470	K00470	K00470

An optional adapter is required when putting a narrower ice machine on a wider bin. * No adapter is needed

Available Accessories See price book for replacement: scoops, legs, specialty legs and casters

K00146 Convenient Ice Bagger

Includes bagger, D-bin adapter, and 250 bags and ties (Not for D320 or D400) Order K00068 replacement bags



K00461 External Scoop Holder

NSF approved. Can be mounted on the left or right side of bins, horizontally or vertically or on a wall.





K00463 Metal Scoop

Indestructible NFS approved aluminum alloy with sanitary knuckle and thumb guard. Works with K00461external scoop holder or hangs inside the D-Bin series. Limited life time guarantee. (Available October 2018)



K00462 **Secure Fastening Kit**

Securely fast the Indigo ice machine head to the pre-drilled inserts on the back of the D-bin series. Stainless steel flanged feet attach to bin and can be screwed to the floor





Welbilt reserves the right to make changes to the design or specifications without prior notice.

2110 South 26th Street Manitowoc, WI 54220

Tel: 1.920.682.0161 Fax: 1.920.683.7589

www.manitowocice.com 6453B 09/18



NR= Not Recommend. Bin too small or too large for application.

Putting a wider machine on narrower bin is not an option. Machines side by side must be water cooled or remote.

Application Bin Capacity shown in lbs using the AHRI rating based on 90% of total volume x 33 lbs/ft3 average density of ice.

Machine capacity shown in lbs/24hrs using the AHRI rating base at 90F ambient, 70F water temperature