

# F-1001M\_J-C

## MODULAR CUBELET ICE MACHINE

### SLIM-LINE SERIES

Item # \_\_\_\_\_

Project: \_\_\_\_\_

Qty: \_\_\_\_\_

\*AutoCad available on KCL

F-1001M\_J-C

4/22/16

Item #13107

#### FLAKER DIMENSIONS


W x D x H

**F-1001M\_J-C**

22 x 27<sup>3/8</sup> x 25<sup>15/16</sup>




B-300




B-500



B-700



B-800



B-900

Also available on Large Bins:


B-1150SS

B-1300SS

B-1500SS

B-1650SS

#### \*CUBELET DIMENSIONS



\*approximate size, image not to scale



#### F-1001MAJ-C

Air-Cooled

Shown on an optional  
B-700

#### F-1001MWJ-C

Water-Cooled

#### F-1001MRJ-C

Remote Air-Cooled

- Up to 910 lbs. of ice production per 24 hours
- Durable stainless steel exterior
- Protected by H-GUARD Plus Antimicrobial Agent
- Advanced CleanCycle24™ Design
- Produces ideal chewable ice
- Longer life and easy maintenance
- R-404A Refrigerant



#### Warranty

Valid in United States, Canada, Puerto Rico, & U.S. Territories. Contact factory for warranty in other countries.

**Three Year** - Parts & Labor on entire machine.

**Five Year** - Parts on Compressor, air-cooled condenser coil.



# HOSHIZAKI

## F-100IM\_J-C CUBELET ICE MACHINE SLIM-LINE MODULAR SERIES

**DIMENSIONS**  
W x D x H  
**F-100IM\_J-C**  
22 x 27<sup>3/8</sup> x 25<sup>15/16</sup>

- Air-cooled
- Water-cooled
- Remote Air-cooled

### AIR-COOLED

Water Temp ° F.	50°	70°	90°
Air Temp ° F.	70°	869	832
	80°	764	731
	90°	700	643

### WATER-COOLED

Water Temp ° F.	50°	70°	90°
Air Temp ° F.	70°	788	770
	80°	734	717
	90°	703	667

### REMOTE AIR-COOLED

Water Temp ° F.	50°	70°	90°
Air Temp ° F.	70°	825	797
	80°	745	720
	90°	683	650

### UTILITY CONSUMPTION

Model Number	KWH per 100 LBS.		Potable Water Gal. per 100 lbs.		Condenser Water Gal. per 100 lbs.	
	90/70	70/50	90/70	70/50	90/70	70/50
F-1001MAJ-C	5.3	3.9	12.0	12.0	N/A	N/A
F-1001MWJ-C	4.1	3.8	12.0	12.0	130	61
F-1001MRJ-C	5.3	4.6	12.0	12.0	N/A	N/A

### SPECIFICATIONS

Model Number	Condenser	Amperage	Min. Circuit Ampacity	Shipping Weight
F-1001MAJ-C	Air-Cooled	15.2	20	210 lbs.
F-1001MWJ-C	Water-Cooled	14.2	20	210 lbs.
F-1001MRJ-C	Remote Air-Cooled	15.7	20	210 lbs.

### STORAGE BINS

Model Number	AHRI-Rated Capacity*
B-300	260 lbs.
B-500	360 lbs.
B-700	550 lbs.
B-800	600 lbs.
B-900	660 lbs.
B-1150	900 lbs.
B-1300	950 lbs.
B-1500	1120 lbs.
B-1650	1210 lbs.

\*Rated in accordance with AHRI Standard 820 (I-P)


### ELECTRICAL & PLUMBING/F-100IM\_J-C

- 115V/60/1
- Icemaker Water Supply Line: Minimum 1/4" Nominal ID Copper Water Tubing or Equivalent
- Icemaker Drain Line: Minimum 3/4" Nominal ID Hard Pipe or Equivalent




© HOSHIZAKI AMERICA, INC.


618 Hwy. 74 S., Peachtree City, GA 30269




FRONT VIEW  
(Air)




SIDE VIEW




ICE DROP ZONE



AIR-COOLED UNIT




WATER-COOLED UNIT



REMOTE AIR-COOLED UNIT

URC-5F Remote Condenser (Sold Separately)  
For Use with F-1001MRJ



Voltage supply for the URC Remote Condenser is supplied from the Ice Maker. No additional circuit is required.

Pre-Charged Tubing Kits (Sold Separately)  
20' R404-2046-2  
35' R404-3546-2

### OPERATING LIMITS

- Ambient Temp Range 45 - 100° F
- Water Temp Range 45 - 90° F
- Water Pressure 10 - 113psig
- Voltage Range 104 - 127V

### OPERATING LIMITS/URC-5F

- Ambient Temp Range -20° F - +122° F
- Voltage Range 104 - 127V

### SERVICE

- Panels easily removed and all components accessible for service.
- Removable/cleanable air filter. (Air-Cooled model only)

TEL 1-800-438-6087

FAX 1-800-345-1325

www.hoshizaki.com

Printed in U.S.A.

