

## E8600 Series (Unheated) **ALUMINUM TRANSPORT & STORAGE CARTS**

Non-Insulated Aluminum with Angle Slides for 18"x26" Sheet pans



Model	Capacity	Inside	Overall Dimensions						Caster		Shipping	
Number	18"x26" Trays	Working	Height		Depth		Width		Diameter		Weight	
	1-1/2" Spacing	Height	in	mm	in	mm	in	mm	in	mm	lbs	kgs
E8623	23	27 <sup>3</sup> / <sub>4</sub>	45 <sup>3</sup> / <sub>8</sub>	1153	30	762	233/4	603	5	127	113	51
E8631	31	39 <sup>3</sup> / <sub>4</sub>	57 <sup>3</sup> /8	1457	30	762	23 <sup>3</sup> / <sub>4</sub>	603	5	127	123	56
E8639	39	51 <sup>3</sup> / <sub>4</sub>	69 <sup>3</sup> / <sub>4</sub>	1762	30	762	23 <sup>3</sup> / <sub>4</sub>	603	5	127	133	60

<sup>\*</sup>Standard capacity fixed on 1-1/2" centers.

**CONSTRUCTION...**Straight line modular styling with all seams hemmed-in for added strength & durability. Heavy gauge aluminum construction is heli-arc welded to form solid unit. Reinforced with horizontal stabilizing bar and welded-on top, corner & bottom reinforcements. Side panels have heli-arc welded interlocking inverted "V"s.

**CABINET MATERIAL...**Entire cabinet constructed heavy gauge aluminum. Top constructed of inner and outer panel, each constructed of .063" aluminum and heli-arc welded into solid piece. Back constructed of .080" thick aluminum, brake formed into "C" type section to join near uprights with extra middle reinforcements. Sides constructed of .075" thick extruded aluminum panels with interlocking, heli-arc welded "V" seams.

BASE FRAME...Constructed of .190" thick aluminum brake formed and heli-arc welded into solid piece. Entire base frame, bolster pads and supports are heliarc welded.

UPRIGHTS... Constructed of 1"x1"x.125" thick extruded aluminum channels. Uprights are heli-arc welded to base and top of cabinet.

CASTERS...5" diameter polyurethane tread casters with Delrin sleeve axle bearing and full ball bearing swivel, plated mounted and bolted to frame.

DOOR...Single panel construction .090" thick aluminum with all sides hemmed in and heli-arc welded.

LATCH...Flush mounted heavy duty sliding stainless steel latch for positive closure.

HINGES...Heavy-duty stainless steel hinges with 270 degree swing. Top and bottom hinges are integrally mounted to cabinet to keep door square.

TRAY SLIDES...Horizontal, .100" aluminum tray slides fixed on 1-1/2" centers.

## **ACCESSORIES/OPTIONS...**

- ☐ Full perimeter bumper
- ☐ Corner bumpers ☐ Swing door catch

Specifications subject to change through product improvement & innovation.

## **CARTER-HOFFMANN**

1551 McCormick Ave., Mundelein, IL 60060 (847) 362-5500 • (800) 323-9793 • Fax (847) 367-8981