



E8600 Series (Unheated) ALUMINUM TRANSPORT & STORAGE CARTS

Non-Insulated Aluminum with Angle Slides for 18"x26" Sheet pans

CARTER-HOFFMANN



FOOD SERVICE EQUIPMENT
ALUMINUM UTILITY CABINETS



E8639

Model Number	Capacity 18"x26" Trays 1-1/2" Spacing	Inside Working Height	Overall Dimensions						Caster Diameter		Shipping Weight	
			Height		Depth		Width		in	mm	lbs	kgs
			in	mm	in	mm	in	mm				
<input type="checkbox"/> E8623	23	27 ³ / ₄	45 ³ / ₈	1153	30	762	23 ³ / ₄	603	5	127	113	51
<input type="checkbox"/> E8631	31	39 ³ / ₄	57 ³ / ₈	1457	30	762	23 ³ / ₄	603	5	127	123	56
<input type="checkbox"/> E8639	39	51 ³ / ₄	69 ³ / ₄	1762	30	762	23 ³ / ₄	603	5	127	133	60

*Standard capacity fixed on 1-1/2" centers.

CONSTRUCTION... Straight line modular styling with all seams hemmed-in for added strength & durability. Heavy gauge aluminum construction is heli-arc welded to form solid unit. Reinforced with horizontal stabilizing bar and welded-on top, corner & bottom reinforcements. Side panels have heli-arc welded interlocking inverted "V"s.

CABINET MATERIAL... Entire cabinet constructed heavy gauge aluminum. Top constructed of inner and outer panel, each constructed of .063" aluminum and heli-arc welded into solid piece. Back constructed of .080" thick aluminum, brake formed into "C" type section to join near uprights with extra middle reinforcements. Sides constructed of .075" thick extruded aluminum panels with interlocking, heli-arc welded "V" seams.

BASE FRAME... Constructed of .190" thick aluminum brake formed and heli-arc welded into solid piece. Entire base frame, bolster pads and supports are heli-arc welded.

UPRIGHTS... Constructed of 1"x1"x.125" thick extruded aluminum channels. Uprights are heli-arc welded to base and top of cabinet.

CASTERS... .5" diameter polyurethane tread casters with Delrin sleeve axle bearing and full ball bearing swivel, plated mounted and bolted to frame.

DOOR... Single panel construction .090" thick aluminum with all sides hemmed in and heli-arc welded.

LATCH... Flush mounted heavy duty sliding stainless steel latch for positive closure.

HINGES... Heavy-duty stainless steel hinges with 270 degree swing. Top and bottom hinges are integrally mounted to cabinet to keep door square.

TRAY SLIDES... Horizontal, .100" aluminum tray slides fixed on 1-1/2" centers.

ACCESSORIES/OPTIONS...

- Full perimeter bumper
- Corner bumpers
- Swing door catch

SPECIFICATIONS

Specifications subject to change through product improvement & innovation.

CARTER-HOFFMANN
1551 McCormick Ave., Mundelein, IL 60060
(847) 362-5500 • (800) 323-9793 • Fax (847) 367-8981
www.carter-hoffmann.com

Printed in U.S.A. J15 0609
Carter-Hoffmann is a trademark
of Carter-Hoffmann LLC