

JOB:	
ITEM NO:	

UNIVERSAL ANGLE ROLL-IN REFRIGERATOR RACKS 207-UA SERIES

FEATURES AND BENEFITS:

- Durable rack specifically designed to fit roll-in or pass through refrigerators, freezers, and warming cabinets; eliminates unnecessary product handling while maintaining proper temperature levels. Holds a variety of pan sizes.
- Fully welded framework of structural aluminum extrusions for rigidity and durability.
- Constructed of non-corrosive, Hi-Tensile aluminum for strength.
- Chrome plated wire universal angles adjustable on 1-1/2" centers. Extruded aluminum bottom angle permanently welded in place.
- Inboard heavy duty 5" swivel casters, two with brakes. Wheel placement permits easy "in-and-out" of roll-ins.
- Two styles available; Custom (C) or Deluxe (D).
 Deluxe includes perimeter bumper and enclosed base.



207-UA-12-AC




ACCESSORIES and OPTIONS (Available at extra cost):


- □ Extra Universal Angles
- □ Pan Stop
- □ Corner Bumpers
- □ Vertical Bumpers
- □ Various Caster Options


See page G-36 for accessory details.


www.crescor.com

207-UA Roll-In Series









INBOARD CASTER PLACEMENT

CUSTOM ("C")

CRES COR MODEL NO.	PAN			DIM "A"	DIM "B"	DIM "C"	INSIDE DIMENSIONS				WEIGHT
	CAP/ ANGLES	SIZE		WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH	HEIGHT		ACT.
207-UA-12-AC	12	SEE NOTE	IN	24-1/2	24-15/16	64-1/2	21-3/4	24-1/2	55-15/16	LBS	68
	SETS	BELOW	MM	625	635	1640	555	625	1425	KG	31

DELUXE ("D")

CRES COR MODEL NO.	PAN			DIM "A"	DIM "B"	DIM "C"	INSIDE DIMENSIONS				WEIGHT
	CAP/ ANGLES	SIZE		WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH	HEIGHT		ACT.
207-UA-12-AD	12	SEE NOTE	IN	26-3/8	26-13/16	64-1/2	21-3/4	24-1/2	55-15/16	LBS	73
207-0A-12-AD	SETS	BELOW	MM	670	685	1640	555	625	1425	KG	33

NOTES: 1. Pan sizes 22" x 20" (560 x 510) Roast & Bake Pans, 10" x 20" (255 x 510) Roast & Bake Pans, 18" x 26" (460 x 660) Bun Pans, 14" x 18" (355 x 460) Service Trays, 12" x 20" (305 x 510) Steam Table Pans.

Refer to Pan Size Chart at end of section.

2. When ordering bumpers, add 2" to overall dimensions.

ALL CONSTRUCTION IS RIVETED, WELDED AND FINISHED.

RACK:

- Posts: Extruded aluminum channels, 1-1/16 x 2 x .125.
- Top and bottom: Extruded aluminum channels, 1-1/16 x 2-3/8 x .188; welded to posts.
- Tie rods (2): 5/16 dia. steel rods enclosed in aluminum tubing; fastened to posts.
- Bolsters: Formed .125 aluminum; welded to posts, casters attached.
- Casters: 5" dia., swivel, modulus tires, 1-1/4 wide, load cap. 250 lbs. each, temp. range -45°/+180°F.
 Delrin bearings. Two casters equipped with brakes.

DELUXE ("D") MODELS:

- · Base plate: One piece .063 aluminum.
- Bumper: 1" wide gray rubber, perimeter type.

PAN SLIDES:

- Wire angles (.306 dia.), nickel chrome plated steel, spaced on 4-1/2" centers, adjustable on 1-1/2" centers.
- · Bottom extruded angle, welded to posts.



5925 Heisley Road • Mentor, OH 44060-1833 Phone: 877/CRESCOR • Fax: 440/350-7267 www.crescor.com

© Crescent Metal Products, Inc. 2011 All rights reserved.

SHORT FORM SPECIFICATIONS

Cres Cor Roll-In Refrigerator Rack Model 207-UA-12-A (\underline{C}) or (\underline{D}). Extruded aluminum welded construction. Tie rods (2) applied at front and rear. (12) sets wire universal angles for multiple pan sizes, adjustable spacing every 1-1/2". Formed .125 bolsters. Inboard 5" swivel modulus casters, Delrin bearings. Load capacity 250 lbs. each, temperature -45° to +180°F.

- Custom Model (C)
- Deluxe Model (D) has .063 aluminum base plate; perimeter bumper.

3-Year Parts / 1-Year Labor warranty. Lifetime guarantee against rust & corrosion. Provide the following accessories:

. NSF listed.

In line with its policy to continually improve its products, CRES COR reserves the right to change materials and specifications without notice.

Litho in U.S.A.