

Features:

- Stainless Steel exterior.
- Rigid stainless steel lift doors withstand heavy use.
- A gasket seals the door opening to reduce ice meltage.
- Non-corroding polyethylene lined walls eliminate pitting and staining.
- Easy cleaning.
- Non-CFC polyurethane foam insulation bonds the shell and lining.
- Extra-large door openings provide maximum access for ice removal and bin cleaning.
- Low door sills allow users to easily reach ice at the bottom of the bin.

ICE BINS



KDB230

- Match with the GT360 Series
- Storage capacity 230 lbs / 104 kg



KDB400

- Match with the GT360 or GT560 Series
- Storage capacity 400 lbs / 181 kg



KDB650

- Match with the GB560 or GB1060 Series
- Storage capacity 660 lbs / 299 kg



KDB950

- Match with the GB1060 or GB560 Series
- Storage capacity 950 lbs / 431 kg

General Specifications for KDB230/KDB400/KDB650/KDB950

Model	Dimensions / inches (cm)			Ice Capacity lb (kg)	Weight lb (kg)
	W	D	H <small>WITH 6" LEGS</small>		
KDB230	30.25" (76.8cm)	34" (86.4cm)	23" (58.4cm)	230lb (104kg)	112lb (51kg)
KDB400	30.25" (76.8cm)	34" (86.4cm)	37" (94cm)	400lb (181kg)	163lb (74kg)
KDB650	42" (106.6cm)	35" (88.9cm)	41" (104.1cm)	660lb (181kg)	182lb (82.5kg)
KDB950	48" (121.9cm)	31.75" (80.6cm)	50" (127cm)	950lb (431kg)	231lb (105kg)

GT360 – ICE MACHINE

THE IMPACT

Even if you don't need a ton of ice, you can still make a large impact with your customers. The KOLD-DRAFT GT360 produces up to 300lbs. of our exclusive FULL cube, and HALF cube ice.

Dimensions/Weight				
Description	Dimensions / inches (cm)			Ship Weight
	W	D	H	
Air Cooled	30.1" (76.5cm)	25.7" (65.3cm)	16.9" (42.9cm)	175lb (79.3kg)
Liquid Cooled	30.1" (76.5cm)	25.7" (65.3cm)	16.9" (42.9cm)	175lb (79.3kg)

Recommended Operating Requirements:

	MIN.	MAX.
Room Air Temp.	45°F (7°C)	110°F (43°C)
Water Temp.	45°F (7°C)	90°F (32°C)
Voltage 208-230	198V	253V
Voltage 115	104V	126V
Potable Water Pressure	20 PSIG (137 kPa)	100 PSIG (689 kPa)
Liquid-Cooled Condenser Pressure	20 PSIG (137 kPa)	100 PSIG (689 kPa)

GT360 Series Daily Capacities: Lbs. of ice per 24 hours per unit

Model Number	Electrical Volt/Hz/Ph	Condenser	Cube Size	Min. Ice Capacity 24 Hours lbs. (kg)		Max. Energy Input 90°F (32°C) 70°F (21°C)	Max. Water Use gal/100# (l/kg)		MCA	MOP	Required Condenser
				70°F (21°C) 50°F (10°C) Ambient/ Water	90°F (32°C) 70°F (21°C) Ambient/ Water		Potable	Condenser			
GT361AC	115/60/1	Air Cooled	Full Cube	352 (160)	282 (128)	6.5 (516)	25.9 (2.2)	n/a	12.0	15	n/a
GT361AHK			Half Cube	372 (169)	286 (130)	6.5 (516)	22.0 (1.8)		12.0	15	
GT361LC		Liquid Cooled	Full Cube	358 (162)	304 (138)	5.2 (413)	19.5 (1.6)	170 (14.2)	11.1	15	
GT361LHK			Half Cube	410 (186)	367 (166)	4.9 (389)	21.0 (1.8)	185 (15.4)	11.1	15	
GT364AC	208-230/60/1	Air Cooled	Full Cube	357 (162)	310 (141)	6.2 (492)	21.3 (1.8)	n/a	6.5	15	
GT364AHK			Half Cube	389 (176)	317 (144)	6.3 (500)	21.3 (1.8)		6.5	15	
GT364LC		Liquid Cooled	Full Cube	349 (158)	295 (134)	5.2 (413)	19.3 (1.6)	168 (14.0)	6.0	15	
GT364LHK			Half Cube	399 (181)	351 (159)	4.9 (389)	22.0 (1.8)	175 (14.6)	6.0	15	

Use Model # GT367AHK, GT367AC, GT367LHK, GT367LC to Indicate 220/50/1.

KOLD-DRAFT

ice Machines • bins • crushers • dispensers



SHOWN WITH B400 BIN

Plumbing:

- 3/4" FPT potable water inlet
- 3/4" FPT bin drain
- 3/4" I.D. flex tubing cuber drain
- 3/8" FPT condenser (liquid-cooled) inlet
- 1/2" FPT condenser (liquid-cooled) outlet

Exterior Finish:

300 Series stainless steel

Refrigeration System:


Thermostatic expansion valve controlled R-404A-HFC

Clearance Requirements:

Allow 4" left side, 8" right side and back, and 6" top for ventilation and utility connections.

Condenser Heat Rejection:

BTUH/kW/Ton
4,700/1.38/0.39 avg.
5,850/1.71/0.49 peak



IT'S NICE TO BE NOTICED™

