

Project:	
Location:	
Item #:	Quantity:
Model #:	

MODEL: IDC-VAR15HFG

**DISPLAY CASES GELATO - Flat Glass** 

Important: Remove products every night and store them inside a regular freezer, to allow proper defrost cycle and cleaning on the equipment.



# **General Strengths**

- Sanitation. Each cabinet has a drain at the bottom of the unit. When cleaning the unit make sure the drain hose is routed to a floor drain.
- Control systems. Higher precision in managing temperature settings. Greater ability to adjust temperature ranges as per the end user's requirement.
- Modular Line. Designed for gelato.
- 100% Tested. All condenser units are tested 100%, in helium chambers to refrigerant leak detections.
- Certified. Audited and Certified by INTERTEK for compliance with UL 471 and NSF 7. AENOR audited and certified by internationally recognized firm. ISO 9001:2008 (Quality); ISO 14001:2004 (Environmental); OSHAS 18001:2007 (Prevention and Worker Safety)
- Lighting. Interior cabinet includes LED lighting, for brighter lighting and energy efficiency. LED saves 90% more energy compared to traditional fluorescent bulbs. Increases product visibility considerably.

MODEL	Dimensions (inches) (mm)			Sides	Nº	Ref.	Ref. Weight	Temp. Range	Capacity (Cu. Ft.)	Cond. Unit.	Case	Crated Weight
	W	D	Н		Pans		(Lbs.) (gr.)	(°F) (°C)	(L)	H.P.	Amps	(Lbs.) (Kg.)
IDC-VAR15HFG	61-1/2	43-7/8	52	1-3/16 +	16	R404A	1.65+1.43	-2°F/+5°F	3.95	1+1/2	6.1 (230V)	660
	1562	1115	1320	1-3/16			750+650	-18°C/-15°C	112		5.4 (115V)	299

1.305.777.9598 Fax

ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 - WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE











Infrico USA Corp. 7042 N.W. 46th Street service@infrico.com Miami, FL 33166 sales@infrico.com 1.305.777.9599 Office

www.infrico.us APPROVALS: AVAILABLE AT:





Project:		
Location:		
Item #:	Quantity:	
Model #:		

MODEL: IDC-VAR15HFG

DISPLAY CASES GELATO - Flat Glass

### STANDARD FEATURES

## Exterior

- White compact quartz worktop,
- Tilt forward frontal tempered glass system,
- DM lacquered decoration, White RAL 9016 or Black RAL 9017 standard decoration,
- Built-in casters and levelling feet.
- Pull down night curtain on the back,

#### > Interior

- AISI 304 Stainless Steel exhibition area,
- LED Lighting in the back and front,
- Case is compatible with standard 5 Liter Gelato Pans (13-1/8"x6-1/2"x5-7/8"), pans included.

#### **OPTIONAL FEATURES**

- ✓ Customizable decoration for lower front and side panels,
- ✓ Optional decoration: Red RAL 3001, Blue RAL 5015, Pink RAL 3504035.
- Electrical connection is 220-230 V / 1ph / 50 Hz (plug) type varies).

### > Insulation

- CFC-Free polyurethane insulation, entire cabinet structure is foamed-in place using a high density polyurethane insulation,
- Low GWP & Zero ODP effect.

## Refrigeration

- Digital temperature controller with automatic hot gas defrost system,
- Temperature display on front,
- Stainless steel evaporative pan,
- Forced air refrigeration system,
- Case engineered to operate at 75°F (25°C). and 55% relative humidity,
- Refrigeration capacity: 4060 Btu/h(-31°F)/ 1190W(-35°C).

## Electrical



- Cord and NEMA L14-30P plug,
- Electrical connection is 230V (Compressor) and 115V (Digital Control) / 1ph / 60 Hz.
- ETL Listed to UL471 Standard and Sanitation classified to NSF7.

## **PLAN VIEW**

**RIGHT VIEW PLAN VIEW ELEVATION** 62%" [1578mm] 61%" [1562mm] 63%" [1622mm] 61½" [1562mm]

ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 - WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE











www.infrico.us service@infrico.com sales@infrico.com

APPROVALS: AVAILABLE AT:

