

**MODEL: IUC-MSG96** **CHEF BASES:**  
**Drawered Refrigerator**



AISI 304 Stainless Steel worktop with drip guard marine edge, standard.

Heavy-duty stainless steel drawer slides designed to hold up to 440 Lbs. (Pans Not Included)

**General Strengths**

- ✓ **Worktop.** Cabinet top is one piece, heavy duty reinforced stainless steel. Drip resistant "V" edge protect against spills.
- ✓ **Drawers.** All drawers include triple chamber door gaskets, easy to remove and snap in. Heavy-duty stainless steel slides hold up to **440 lbs.** Integrated handle and self-closing device.
- ✓ **Control systems.** Higher precision in managing temperature settings. The ability to adjust temperature ranges to meet end user's requirements.
- ✓ **100% Tested.** All condensing units are 100% tested in helium chambers in order to detect refrigeration leaks.
- ✓ **Certified.** Audited and Certified by **INTERTEK** for compliance with UL 471 and NSF 7. AENOR audited and certified by internationally recognized firm. ISO 9001:2008 (Quality); ISO 14001:2004 (Environmental); OSHAS 18001:2007 (Prevention and Worker Safety)

MODEL	Dimensions (inches) (mm)			Nº Drawers	Nº Pans	Ref.	Ref. Weight (Lbs.) (gr.)	Temp. Range (°F) (°C)	Capacity (Cu. Ft.) (L)	Cond. Unit. H.P.	Case Amps 115 V.	Crated Weight (Lbs.) (Kg.)
	W	D	H									
IUC-MSG96	97 2464	32-1/2 825	26-1/4 666	4	12	R134a	0.79 360	33°F/38°F 0°C/4°C	20.6 584	1/3	6.7	507 230

ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 – WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE

**MODEL: IUC-MSG96**
**CHEF BASES:  
Drawered Refrigerator**
**STANDARD FEATURES**
**➤ Exterior**

- AISI 304 Stainless Steel Top. Drip resistant “V” edge protects against spills,
- Front and sides in AISI 430 Stainless Steel.

**➤ Interior**

- AISI 430 Stainless Steel,
- Sealed interior floors.

**➤ Casters**

- 4” diameter casters,
- Locks provided on front set.

**➤ Drawers**

- Each drawer accommodates two full 12”x20” pans (pans not included),
- Drawers with full-extension sliding rails for complete opening,
- Drawers with integrated handle,
- **Heavy-duty stainless steel drawer slides designed to hold up to 440 Lbs (200 Kg).**

**➤ Insulation**

- CFC-Free polyurethane insulation, entire cabinet structure is foamed-in place using a high density polyurethane insulation,
- Low GWP & Zero ODP Effect.

**➤ Refrigeration**

- Digital temperature controller with automatic defrost system,
- Stainless steel evaporative pan,
- **Compact refrigeration system monoblock, INFRIBLOCK®,**
- **Extractable condensing unit for easy service,**
- Evaporator coil coated with anti-corrosion material 100% Polyester,
- Front-breathing refrigeration system,
- Forced air refrigeration system,
- Refrigeration capacity: 1550 Btu/h (14°F)/ 454 W (-10°C).


**➤ Electrical**

- Cord and NEMA 5-15P plug,
- Electrical connection is 115V / 1ph / 60 Hz.


**OPTIONAL FEATURES**

- ✓ Set of 6” legs, height adjustable from 5” to 8”,
- ✓ Electrical connection is 220-230 V / 1ph / 50 Hz (plug type varies).

- **ETL Listed to UL471 Standard and Sanitation classified to NSF7.**

**PLAN VIEW**
**ELEVATION**
**RIGHT VIEW**
**PLAN VIEW**


ETL LISTED TO UL471 STANDARD AND SANITATION CLASSIFIED TO NSF7 – WE RESERVE THE RIGHT TO CHANGE SPECIFICATIONS WITHOUT PRIOR NOTICE